Product Environmental Aspects Declaration

EP and IJ printer (PCR-ID:AD-04)



No. AD-13-E251 Date of publication Feb./1/2013



http://konicaminolta.jp

Please direct any inquiries or comments to e-mail: bt-environ@pub.konicaminolta.jp



Total of 216,600 sheets on the assumption of five years usage.

Environmental impact by copypaper is not included

Auto Document Feeder is optional.

bizhub 195

Marking technologies Electrophotographic Printer (EP)

Printing speed 19 prints-per-minute(B/W)

optional

Maximum copy paper A3

Duplex copying optional


Life Cycle Impact

Document feeding

Consumption and discharge in a life cycle	All the stage sum totals			
Global warming(CO₂equivalent):kg	395			
Global Warming(OO2Oquivalone).ikg	(346)			
Acidification(SO ₂ equivalent):kg	0.5			
Acidinoation(00 gequivalent).kg	(0.5)			
Energy resources(crude oil equivalent):MJ	7,291			
Lifergy resources(crude oil equivalent/.iwo	(6,272)			

**Figures in() indicated environmental impact including recycle effect *note3

Warming load CO₂ equivalent of each stage(kg)



Notes

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at http://www.ecoleaf-jemai.jp/eng/ for details.
- 3. Recycle Effect illustrates an indirect influence to other products/services.
- 4. Basic Units used for calculations are based on Japan domestic data at this time, due to a lack of base data to establish localized Basic Unit for overseas locations adequately.
- 5. This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

(Supplemental environmental information)



- Certified Environmental Standards
 - International Energy Star Program

 $PCR\ review\ was\ conducted\ by\ :\ PCR\ Deliberation\ Committee, January\ 01,2008, Name\ of\ reprentative\ :\ Youji\ Uchiyama,\ University\ of\ Tsukuba, Graduate\ School$

Independent verification of the declaration and data, according to ISO14025 $\ \Box$ internal $\ \blacksquare$ external

Third party verifier: The third party verifier * : Shozo Nakamuta

Program operator: Japan Environmental Management Association for Industry, ecoleaf@jemai.or.jp

^{*} In the case of a business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

to Soil system

Product Environmental Information Data Sheet (PEIDS)

Document control no.	F-02B-03	Unit Function DB version	2.1
Product vendor	KONICA MINOLTA ,INC.	Characterization Factor DB version	2.1
EcoLeaf registration no.	AD-13-E251		



	PCF	PCR name EP and IJ printer Product type bizhub 195								
	PC	R-ID	AD-04		Product weight[kg]	26.5	Package[kg]	9.3	Weight total[kg]	35.8
			116- 01- 01		Dund	esti e u	0 1 62		0 102	
In/O	ut ite	me	Life Cycle Stage	Unit	Produ Raw material	Product	Distribution	Use	Disposal	Recycle
,0	ut ite	1113		MJ	2.53E+03	9.31E+02	9.01E+01	3.71E+03	2.81E+01	-1.02E+03
		Energy C	onsumption	Mcal	6.04E+02	2.22E+02	2.15E+01	8.87E+02	6.70E+00	-2.43E+02
			Coal		1.80E+01	1.69E+00	2.13E+01 2.11E-04	1.78E+01	1.48E-01	-7.02E+00
			Crude oil (as a fuel)	kg	2.44E+01	3.23E+00	1.97E+00	2.52E+01	3.00E-01	-8.43E+00
		Energy	Natural Gas	kg kg	4.19E+00	1.25E+01	3.04E-02	1.02E+01	7.67E-02	-1.08E+00
			Uranium ore	mg	4.58E-04	1.14E-04	1.43E-08	9.63E-04	1.00E-05	-8.40E-05
				IIIg	4.JOE 04	1.146 04	1.432 00	9.03E 04	1.00E-03	-0.40E-03
			Crude oil (as an ingredients)	kg	1.03E+01	0	0	1.34E+01	0	-7.39E+00
			Iron ore	kg	1.34E+01	0	0	3.20E+00	0	-6.61E+00
			Copper ore	kg	3.62E-01	0	0	2.41E-03	0	-1.04E-01
			Bauxite	kg	1.85E-01	0	0	3.29E-01	0	-2.05E-01
	ption	es es	Nickel ore	kg	2.14E-02	0	0	3.55E-02	0	-2.27E-02
	sum	aust	Chromium ore	kg	3.33E-02	0	0	4.91E-02	0	-3.30E-02
	Cor	Exhaustible resources	Manganese ore	kg	7.06E-02	0	0	2.27E-02	0	-7.56E-03
	Resource Consumption from the environment	Material	Plumbous ore	kg	1.91E-02	0	0	0	0	-4.48E-03
	Resc		Tin ore	kg	0	0	0	0	0	0
			Zinc ore	kg	1.88E-01	0	0	0	0	-4.41E-02
			Gold ore	kg	0	0	0	0	0	0
			Silver ore	kg	0	0	0	0	0	0
			Silica sand	kg	1.57E+00	0	0	8.54E-02	0	-5.53E-01
			Rock salt	kg	7.94E+00	1.63E-04	0	2.29E-01	9.37E-03	-3.12E+00
Inventory analyses			Limestone	kg	3.22E+00	0	0	7.40E-01	1.71E-01	-1.26E+00
anal			Natural soda ash	kg	1.55E-01	0	0	5.45E-03	0	-5.72E-02
tory		Renewable	Wood	kg	1.20E+01	0	0	6.25E+00	0	-7.28E+00
nver		resources	Water	kg	1.04E+04	1.35E+03	1.59E-01	1.20E+04	1.22E+02	-2.22E+03
_			CO2	kg	1.36E+02	4.74E+01	6.39E+00	1.68E+02	1.72E+01	-4.76E+01
			SOx	kg	8.04E-02	1.05E-02	4.19E-03	1.18E-01	9.22E-03	-2.85E-02
			NOx	kg	1.64E-01	5.83E-02	3.54E-02	1.76E-01	2.18E-02	-6.55E-02
			N2O	kg	1.18E-02	4.02E-02	1.00E-03	1.58E-02	2.80E-05	-5.01E-03
		to Atmosphere	CH4	kg	1.22E-03	3.06E-04	3.81E-08	2.57E-03	2.68E-05	-2.21E-04
			СО	kg	1.75E-02	7.70E-03	1.02E-02	2.88E-02	4.52E-03	-6.70E-03
			NMVOC	kg	2.39E-03	5.99E-04	7.47E-08	5.03E-03	5.26E-05	-4.33E-04
	ge t		СхНу	kg	5.80E-03	6.47E-03	9.94E-04	4.73E-03	1.16E-04	-2.49E-03
	char		dust	kg	1.85E-02	5.66E-04	3.28E-03	1.40E-02	1.27E-03	-7.98E-03
	/Dis		BOD	kg	_	_	_	_	_	-
	Emission/Discharge to the environment		COD	kg	-	_	-	-	-	_
	Em t	to Water system	N total	kg	_	_	_	-	-	-
			P total	kg	-	_	-	-	-	-
			SS	kg	-	_	-	-	-	_
			Unspecified solid waste	kg	8.38E-01	2.39E-04	0	3.78E+00	1.14E+01	-4.22E-01
			Slag	kg	4.46E+00	0	0	9.96E-01	0	-1.94E+00
		to Soil system	Sludge	kg	2.76E-01	0	0	7.06E-01	0	-3.93E-01
			Low emission radioactive waste	kg	3.21E-04	7.99E-05	9.97E-09	6.71E-04	7.00E-06	-5.88E-05
	umption		Energy resources (crude oil equivalent)	kg	4.48E+01	2.04E+01	2.01E+00	5.67E+01	5.70E-01	-1.49E+01
Ŧ.	by Resource Consumption	Exhaustible resources	Mineral resources (Iron ore equivalent)	kg	1.23E+02	0	0	4.04E+01	0	−5.17E+01
smen	by Re									
Se			Global warming (CO2 equivalent)	kg	1.40E+02	5.82E+01	6.66E+00	1.73E+02	1.73E+01	-4.89E+01
t as	۔ د	to	A 1 1101 41	kg	1.95E-01	5.13E-02	2.90E-02	2.41E-01	2.45E-02	-7.43E-02
Impact assesment	issior	Atmosphere	(SO2 equivalent)	5	1.002 01	VUL VL	2.002 02	2.112 01	E. 10E 02	7.102 02
=	by Emi Sonsun	Atmosphere to Water system								

[Notes for readers: EcoLeaf common rules]

I. Stage related

- A. "Production" stage is intended for two sub-stages listed below.
 (1) "Raw material" production: consists of mining, transportation and raw material production.
 - (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts)
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal/recycle of consumable
- D. "Disposition/Recycle" stage is intended for environmental impacts by product disposition/recycle, and deduction by recycling

 E. "Recycle Effect" illustrates an indirect environmental influences to other products/services by use of reclaimed materials/parts, and/or by supply of
- Case 1: Use of reclaimed materials/parts: Sum of increase of environmental impact by collection activities of used materials/parts, and decrease Case 2: Supply of used products to other businesses for material reclaim/parts reuse: Sum of increase of environmental impact by materials/parts

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.

 B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate,
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO2 in case of "Global Warming"

A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.

B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

IV Data entry format

- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results. C. Indicate "-" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".

(BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

- A."Raw material" in "Production" includes environmental impacts generated during mining transportation material production phases of the main body B. "Product" in "production" includes environmental impacts of processing of the parts (injection, blow-, press- and glass-molding).

 C. Regarding the basis and the basic units for calculations during distribution stages


- D. Regarding the basis and the basic units for calculations during use and consumption stage

 E. The recycling impacts are calculated assuming that 40% of the end-of-life printers are recovered from users according to PCR (AD-04).
- F. The impacts of materilal production of recycled materials are included in the values with minus as a recycling effect.

This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

Product data sheet

(Input data and parameters for LCA)





PCR name	EP and IJ printer (PCR-ID:AD-04)		Product type	bizhub 195			
LCA/LCIA in units of:	1	Product weight[kg]	26.5	Package[kg]	9.3	Weight total[kg]	35.8

1. Product information (per unit): parts etc. by material and by process/assembly method

	Breakdown of primar	y materials		Math breakdown of pa	rts, which need to appl	ly Processing / Assembly	Base Units (Parts B, C)
Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
Ordinary steel	1.28E+01	Paper	3.26E+00	Press molding:Iron	1.21E+01	Parts assembly	2.64E-01
Stainless steel	1.34E-01	Rubber	9.34E-02	Press molding:Nonfer rous metal	4.00E-01		
Aluminium	1.22E-01	Semiconductor circuit board	1.09E+00	Injection molding	1.12E+01		
Other metals	2.80E-01			Blow molding	1.00E-01		
Glass	1.53E+00			Glass molding	1.53E+00		
Thermoplastic resin	1.15E+01						
Thermosetting resin	0						
Wood	5.01E+00						
Subtotal	3.14E+01	Subtotal	4.45E+00				
	Total		3.58E+01	Subtotal	2.53E+01	Subtotal	2.64E-01

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO2, NO2 equivalent.

c	Classification	Energy	Energy	Material	Material		
.ej	Distribution	Electricity	Furnace urban	Tapwater	Groundwater		
Ę	Distribution	(kWh)	gas (m³)	(kg)	(kg)		
Cons	Quantity	3.12E+00	1.48E+01	1.45E+01	5.13E+01		
0	Note						
Emission/ Discharge	Classification	To Water system					
rissi	Distribution	Sewage(kg)					
Er Dis	Quantity	2.81E+01					
	Note						

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

	Means of transportation	Freight by ship	Diesel truck	Diesel truck				
	tio	iviearis or transportation	Treight by Ship	:20ton	:2ton			
	뢽	Conditions	Load(kg·km)	Load(kg·km)	Load(kg·km)			
	Dist	Quantity	9.17E+04	2.21E+04	1.50E+03			
		Note						

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
Product	Distribution	Electricity (kWh)	Gasoline as fuel(kg)	Furnace urban gas (m³)	Groundwater (kg)	Ordinary steel (kg)	Stainless steel (kg)	Aluminium (kg)	Copper(kg)
<u>~</u>	Quantity	2.29E+02	3.12E-01	3.05E+00	4.98E+02	3.01E+00	2.24E-01	3.11E-01	7.98E-03
	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Processing	Processing	Processing	Processing
Product	Distribution	Glass(kg)	Thermoplastic resin(kg)	Paper(kg)	Rubber(kg)	Press:Iron(kg)	Press: Nonferrous(kg)	Injection molding(kg)	Blow molding (kg)
<u>~</u>	Quantity	6.50E-02	1.35E+01	2.94E+00	1.86E-01	4.12E+00	3.28E-01	2.72E-02	9.75E+00
	Note								
	Classification	Assembly	To Water system	Distribution	Distribution	Distribution			
Product	Distribution	Parts assembly (kg)	Sewage(kg)	Freight by ship (kg·km)	Diesel truck: 20ton (kg•km)	Diesel truck: 10ton (kg•km)			
	Quantity	9.75E+00	3.13E+02	8.59E+03	4.98E+03	3.13E+03			
	Note								
	Classification								
Product	Distribution								
_	Quantity								
	Note								

4.2 Disposition/Recycle information on consumables and replacement parts

1.2 DISPO	sition/Recycle information on co	nsumables and i	replacement par	ts					
SS	Classification	Consumption	Consumption	Treatment	Treatment	Treatment	Treatment	Treatment	Treatment
umables	Distribution	Electricity (kWh)	Kerosene(kg)	Recycle: to iron(kg)	Recycle: to Aluminum(kg)	Recycle: to copper(kg)	Recycle: to Glass(kg)	Recycle: to plastics(kg)	Recycle: to Paper(kg)
Consul	Quantity	3.62E-01	4.64E-03	1.29E+00	1.24E-01	3.19E-03	2.60E-02	3.51E+00	1.17E+00
0	Note								
	Classification	Treatment	Treatment	Treatment	Treatment	Deduction	Deduction	Deduction	Deduction
nsumables	Distribution	Industrial waste destruction by fire(kg)	Industrial waste inning(kg)	Waste destruction by fire(kg)	Waste inning(kg)	Iron(kg)	Aluminum(kg)	Copper(kg)	Glass(kg)
Consi	Quantity	7.44E-02	3.55E-02	7.20E+00	2.17E+00	-1.29E+00	-1.24E-01	-3.19E-03	-2.60E-02
	Note								
	Classification	Deduction	Deduction	Distribution	Distribution				
sumables	Distribution	Plastics(kg)	Paper(kg)	Diesel truck: 10ton (kg•km)	Diesel truck: 4ton (kg•km)				
Cons	Quantity	-3.51E+00	-1.17E+00	7.50E+02	9.07E+02				
	Note								

5. Disposition/Recycle stage information (per product): process method and scenarios

J. Disposi	Disposition/Recycle stage information (per product): process method and scenarios									
S	Classification	Consumption	Consumption	Treatment	Treatment	Treatment	Treatment	Treatment	Treatment	
umables	Distribution	Electricity (kWh)	Kerosene(kg)	Recycle: to iron(kg)	Recycle: to Aluminum(kg)	Recycle: to copper(kg)	Recycle: to Glass(kg)	Recycle: to plastics(kg)	Recycle: to Paper(kg)	
Consul	Quantity	8.31E-01	1.06E-02	5.17E+00	4.87E-02	2.60E-01	6.12E-01	4.55E+00	3.46E+00	
0	Note									
	Classification	Treatment	Treatment	Treatment	Treatment	Treatment	Deduction	Deduction	Deduction	
Consumables	Distribution	Recycle: to Assembled circuit board(kg)	Incineration: Industrial waste(kg)	Landfill: Industrial waste(kg)	Incineration to landfill (as ash)(kg)	Landfill: General waste(kg)	Iron(kg)	Aluminium (kg)	copper(kg)	
Ŝ	Quantity	1.48E-01	3.03E-01	7.54E-02	1.19E+01	9.50E+00	-5.17E+00	-4.87E-02	-2.60E-01	
	Note									
	Classification	Deduction	Deduction	Deduction	Deduction	Distribution	Distribution			
sumables	Distribution	Glass(kg)	Plastics(kg)	Paper(kg)	Recycle: to Assembled circuit board(kg)	Diesel truck: 10ton (kg•km)	Diesel truck: 4ton (kg•km)			
Consu	Quantity	-6.12E-01	-4.55E+00	-3.46E+00	-1.48E-01	1.72E+03	2.08E+03			
	Note									

6. Others

A.Product information:

All the parts mass per unit sorted by materials and by processes/assembly are included. The motor mass is included in ordinary steel.

B.Production site information:

The energy consumption & material use during the main body assemby and cartridge & toner shipment are included. The environmental impacts that are exhausted from the production site in the atmosphere and the water system are included.

C.Distribution stage information:

The total distance of the transportation in Japan of 100km is used according to PCR (AD-04) and the transportation overseas includes the transportation by track in China and by ship between China and Japan.

D. Product and accessories subject to this analysis:

b. Product and accessories subject to this analysis:

The power consumption is calculated assuming the use period of five years and 216,600 sheets printed during the use period according to the PCR (AD-04).

The toner consumption is summed up over the five years from the toner consumption data per sheet using our print pattern with 5% coverage.

The production impacts of the cartridges and toner used during the use period of five years included.

The impacts of the maintenance parts used and the transportation impacts of the maintenace during the use period of five years are included.

E. Disposal/Recycle information on the consumables and the maintenance parts during use stage:

The recycling information of the toner, the developer, the drums and the maintainance parts used during the use period of five years are included.

The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus.

F.Disposal/Recycle stage information:
The information on the products recovered from users is included.
The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus.

This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.