

Third party verifier: The third party verifier * : Kazuo Naito

Programme operator: Japan Environmental Management Association for Industry, ecoleaf@jemai.or.jp

* In the case of an business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

Form 2 (F-02B-03)

Product Environmental Information Data Sheet (PEIDS)

Document control no. F-02B-03							Unit Fu	nction DB version	2.1	٦ ^ا	ECO	
Product vendor KONICAM						-	Characterization Factor DB version		2.1		LISATO	
EcoLeaf registration no. AD-16-718						,	Unaracterization ractor bb version					
	PCI	Rn	ame	EP and IJ r	rintor	Product type			bizhub 758			
		CR-				Product weight[kg]	201.0	Package[kg]	29.2	Weight total[kg]	230.2	
									20.2	Weight total[kg]	200.2	
Life Cycle Stage Unit Raw material						-	Product	Distribution	Use	Disposal	Recycle	
	<u>ut 110</u>				MJ	1.20E+04	2.49E+03	4.52E+02	2.36E+04	1.34E+02	-4.31E+03	
	Energy Consumption					2.86E+03	5.96E+02	1.08E+02	5.63E+03	3.19E+01	-1.03E+03	
				Coal	kg	1.50E+02	1.68E+01	1.06E-03	1.22E+02	6.39E-01	-6.44E+01	
			Energy	Crude oil (as a fue	el) kg	9.22E+01	1.90E+01	9.88E+00	1.67E+02	1.56E+00	-2.76E+01	
				Natural Gas	kg	1.93E+01	8.66E+00	1.53E-01	6.70E+01	3.34E-01	-5.33E+00	
				Uranium ore	mg	1.81E-03	1.14E-03	7.15E-08	5.65E-03	4.32E-05	-2.40E-04	
				Crude oil (as an ingredients)	kg	3.37E+01	0	0	7.92E+01	0	-1.62E+01	
				Iron ore	kg	1.48E+02	0	0	3.46E+01	0	-6.99E+01	
				Copper ore	kg	3.49E+00	0	0	1.10E-03	0	-1.24E+00	
	u t	e		Bauxite Nickel ore	kg	2.13E+00	0	0	3.13E+00	0	-2.09E+00	
	umpti	Exhaustible	resources	Chromium ore	kg kg	4.14E-01 6.08E-01	0	0	5.84E-01 8.03E-01	0	<u>-3.99E-01</u> -5.63E-01	
	Const	Exhau	reso	Manganese ore		7.94E-01	0	0	2.77E-01	0	-9.61E-01	
	Resource Consumption from the environment		Material	Plumbous ore	kg	1.32E-01	0 0	0	0	0	-4.21E-02	
	Resou	Trom t		Tin ore	kg	0	Ő	0	0	0	0	
	Ľ.,			Zinc ore	kg	1.30E+00	0	0	0	0	-4.14E-01	
				Gold ore	kg	0	0	0	0	0	0	
				Silver ore	kg	0	0	0	0	0	0	
				Silica sand	kg	4.34E+00	0	0	4.02E-01	0	<u>-1.24E+00</u>	
es				Rock salt Limestone	kg	2.43E+01	2.45E-03	0	2.25E+00	7.97E-02	-4.60E+00	
Inventory analyses				Natural soda as	kg	2.88E+01 2.59E-01	0	0	7.42E+00 1.98E-04	6.56E-01 0	<u>-1.13E+01</u> -7.99E-02	
ory ai		Bas	owoble	Wood	n kg kg	4.14E+01	0	0	8.94E+01	0	-5.23E+01	
vent		Renewable resources		Water	kg	4.11E+04	1.33E+04	7.93E-01	7.73E+04	5.22E+02	-1.12E+04	
5				CO2	kg	7.37E+02	1.31E+02	3.21E+01	1.13E+03	6.74E+01	-2.66E+02	
		to Atmosphere		SOx	kg	4.35E-01	9.98E-02	2.37E-02	7.82E-01	3.67E-02	-1.72E-01	
				NOx	kg	7.59E-01	8.04E-02	2.24E-01	1.35E+00	9.79E-02	-2.93E-01	
				N2O	kg	4.83E-02	2.24E-03	4.36E-03	1.23E-01	1.43E-04	-1.78E-02	
				CH4	kg	4.81E-03	3.04E-03	1.91E-07	1.50E-02	1.16E-04	<u>-6.06E-04</u>	
				CO NMVOC	kg	1.22E-01	1.95E-02	7.29E-02	1.97E-01	2.29E-02	-4.69E-02	
	e +			CxHy	kg kg	9.40E-03 2.62E-02	5.97E-03 4.41E-04	3.75E-07 5.72E-03	2.95E-02 3.65E-02	2.26E-04 7.36E-04	<u>-1.19E-03</u> -9.68E-03	
	charg			dust	kg kg	9.72E-02	4.41E-04 4.28E-03	1.98E-02	1.04E-01	5.96E-03	-3.93E-03	
	Emission/Discharge to the environment			BOD	kg	-	-	-	-	-	-	
	ission the er			COD	kg	-	_	-	-	-	_	
	to t	to V	/ater system	N total	kg	-	-	-	-	-	-	
				P total	kg	-	-	-	-	-	_	
				SS	kg	-	-	-	-	-	-	
				Unspecified solid w		3.89E+00	1.85E-02	0	3.74E+01	9.84E+01	-1.65E+00	
		to S	oil system	Slag Sludge	kg kg	4.60E+01 2.79E+00	0	0	1.08E+01 6.71E+00	0	-2.05E+01 -3.80E+00	
			,	Low emission radioactive wast	ka	1.27E-03	7.96E-04	5.00E-08	3.94E-03	3.01E-05	-1.68E-04	
	umption			Energy resource (crude oil equivale	s ka	2.26E+02	4.96E+01	1.01E+01	3.73E+02	2.72E+00	-7.73E+01	
ient	by Resource Consumption		haustible sources	Mineral resource (Iron ore equivale	s ka	1.22E+03	0	0	5.51E+02	0	-6.42E+02	
sesn	ion			Global warming (CO2 equivalent)	kg	7.50E+02	1.32E+02	3.32E+01	1.16E+03	6.74E+01	-2.70E+02	
Impact assesment	Emision Consumption	At	to nosphere	Acidification	kg	9.66E-01	1.56E-01	1.81E-01	1.73E+00	1.05E-01	-3.78E-01	
Ē	ision Co		o Water system									
	by Em		to Soil system									

[Notes for readers: EcoLeaf common rules]

- I. Stage related
- A. "Production" stage is intended for two sub-stages listed below.
 - "Raw material" production: consists of mining, transportation and raw material production.
 "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal/recycle of consumables /maintenance goods (e.g. replacement parts).
- D. "Disposition/Recycle" stage is intended for environmental impacts by product disposition/recycle, and deduction by recycling
- (e.g. impact reduction of raw material production).
- E. "Recycle Effect" illustrates an indirect environmental influences to other products/services by use of reclaimed materials/parts, and/or by supply of used products to other businesses for material reclaim/parts reuse.
- Case 1: Use of reclaimed materials/parts: Sum of increase of environmental impact by collection activities of used materials/parts, and decrease by volume reduction of used materials/parts.
- Case 2: Supply of used products to other businesses for material reclaim/parts reuse: Sum of increase of environmental impact by materials/parts reclaiming process, and decrease by volume reduction of new materials/parts production.

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.
- B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate,
- which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III Impact analyses

- Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO2 in case of "Global Warming") A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.
- B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

IV Data entry format

- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.
- C. Indicate "-" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
- (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

- A."Raw material" in "Production" includes environmental impacts generated during mining transportation material production phases of the main body of the printer and the toner cartridge enclosed in the printer. The environmental impacts are calculated using the eco-leaf basic unit DB for calculations.
- B. "Product" in "production" includes environmental impacts of processing of the parts (injection, blow-, press- and glass-molding). The environmental impacts from the parts assembly plant which is different from the main body assembly plant (such parts are clacified in "parts C") are calculated using the eco-leaf basic unit DB for calculations.
- The impacts from the main body assembly plant are calculated using the quantitative data on environmental impacts in our assembly plant. C. Regarding the basis and the basic units for calculations during distribution stages The total distance of the transportation in Japan of 100km is used according to PCR (AD-04) and the transportation overseas includes
- The total distance of the transportation in Japan of 100km is used according to PCR (AD-04) and the transportation overseas includes the transportation by track in China and by ship between China and Japan.
- D. Regarding the basis and the basic units for calculations during use and consumption stage The power consumption is measured by the TEC test procedure according to PCR (AD-04). 3,375,000 sheets are printed in total during the use period of five years.

The toner consumption is summed up over the five years from the toner consumption data per sheet using our print pattern with 5% coverage. The production loads and the collection & recycling impacts of the toner cartridges used over the five years are included in this stage.

- E. The recycling impacts are calculated assuming that 40% of the end-of-life printers are recovered from users according to PCR (AD-04). The impacts are calculated with the remaining 60% following the disposal senario as general wastes.
- F. The impacts of material production of recycled materials are included in the values with minus as a recycling effect.

Form3 (F-03-03)



230.2

blzhub 758 Weight total[kg]

Product data sheet (Input data and parameters for LCA) F-03-03 KONICAMINOLTA,INC. AD-16-718 Document control no. Product vendor EcoLeaf registration no. EP and IJ printer (PCR-ID:AD-04) PCR name LCA/LCIA in units of: Product type 201.0 29.2 ackage[kg]

1. Product information (per unit): parts etc	. by material and b	y process/assembly method					
	Breakdown of prim	Math breakdown of parts, which need to apply Processing / Assembly Base Units (Parts B, C)					
Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
Ordinary steel			Rubber 8.67E-01 Semiconductor circuit board 3.61E+00		1.34E+02		
Stainless steel					4.96E+00		
Aluminium				Injection molding	4.81E+01		
Other metals	3.73E+00						
Glass	2.02E+00						
Thermoplastic resin	4.81E+01						
Wood	Wood 1.33E+01						
Paper	Paper 1.32E+01						
Subtotal	2.25E+02	Subtotal	4.48E+00				
	Total					Subtotal	

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site. SOx and NOx should be indicated in SO2, NO2 equivalent.

	01 17 11	_	_						
-	Classification	Energy	Energy	Material	Material				
sumption		Electricity (kWh)	Furnace urban gas (m ³)	Industrial water(kg)	Groundwater (kg)				
Const	Quantity	8.74E+01	2.99E-01	4.90E+02	2.47E+01				
Ŭ	Note								
Emission/ Discharge	Classification	To Water system							
schi	Distribution	Sewage(kg)							
	Quantity	4.23E+02							
	Note								
3. Distrib	. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.								
Distribution	Means of transportation	Freight by ship	Diesel truck :20ton	Diesel truck :2ton					
shibu	Conditions	Load(kg+km)	Load(kg+km)	Load(kg · km)					
ä	Quantity	3.91E+05	1.85E+05	1.50E+03					
	Note								

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance. 4.1 Product and accessories subject to this analysis

4.1 Product and accessories subject to this analysis									
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
Product	Distribution	Electricity (kWh)	Gasoline as fuel(kg)	Furnace urban gas (m ³)	Industrial water(kg)	Groundwater (kg)	Ordinary steel (kg)	Stainless steel (kg)	Aluminium (kg)
ē.	Quantity	1.31E+03	1.96E+00	2.45E+01	1.28E+02	3.58E+03	3.22E+01	3.69E+00	2.96E+00
	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Processing	Processing	Processing	Processing
Product	Distribution	Thermoplastic resin(kg)	Paper(kg)	Rubber (kg)	Semiconductor circuit board (kg)	Press:Iron(kg)	Press: Nonferrous(kg)	Injection molding (kg)	Blow molding (kg)
	Quantity	7.99E+01	4.05E+01	1.81E+00	8.00E-03	3.04E+01	1.80E+00	2.22E+01	3.39E+01
	Note								
-	Classification	Assembly	To Water system						
Product	Distribution	Parts assembly (kg)	Sewage(kg)						
	Quantity	3.39E+01	2.67E+03						
	Note								
	Classification	Distribution	Distribution	Distribution					
Product	Distribution	Freight by ship (kg·km)	Diesel truck: 20ton (kg•km)	Diesel truck: 10ton (kg•km)					
	Quantity	1.51E+05	3.55E+04	1.89E+04					
	Note								
4.2 Dispo	osition/Recycle information on co	onsumables and rep	placement parts						
	Classification	Consumption	Consumption	Treatment	Treatment	Treatment	Treatment	Treatment	Treatment
Consumables	Distribution	Electricity (kWh)	Kerosene(kg)	Recycle: to iron(kg)	Recycle: to Aluminum(kg)	Recycle: to copper(kg)	Recycle: to plastics(kg)	Recycle: to Paper(kg)	Industrial waste destruction by fire(kg)
0	Quantity	1.96E+00	3.66E-02	1.17E+01	1.18E+00	1.09E-03	9.64E+00	1.75E+01	1.31E+00
	Note								
	Classification	Treatment	Treatment	Treatment	Deduction	Deduction	Deduction	Deduction	Deduction
Consumables	Distribution	Industrial waste inning(kg)	Waste destruction by fire(kg)	Waste inning(kg)	lron(kg)	Aluminum(kg)	Copper(kg)	Plastics(kg)	Paper(kg)
õ	Quantity	9.75E-02	4.19E+01	2.81E+01	-1.17E+01	-1.18E+00	-1.09E-03	-9.64E+00	-1.75E+01
	Note								
	Classification	Distribution	Distribution						
Consumables	Distribution	Diesel truck: 10ton (kg•km)	Diesel truck: 4ton (kg•km)						
G	Quantity	5.60E+03	6.78E+03						
	Note	0.002.00	0						

5. Disposition/Recycle stage information (per product): process method and scenarios

ŝ	Classification	Consumption	Consumption	Treatment	Treatment	Treatment	Treatment	Treatment	Treatment
umables	Distribution	Electricity (kWh)	Kerosene(kg)	Recycle: to iron(kg)	Recycle: to Aluminum(kg)	Recycle: to copper(kg)	Recycle: to Glass(kg)	Recycle: to plastics(kg)	Recycle: to Paper(kg)
Const	Quantity	3.86E+00	7.21E-02	5.74E+01	4.91E-01	1.99E+00	8.06E-01	8.75E+00	1.11E+01
0	Note								
	Classification	Treatment	Treatment	Treatment	Treatment	Deduction	Deduction	Deduction	Deduction
nsumables	Distribution	Incineration: Industrial waste(kg)	Landfill: Industrial waste(kg)	Incineration to landfill (as ash)(kg)	Landfill: General waste(kg)	Iron(kg)	Aluminium (kg)	copper(kg)	Glass(kg)
Cons	Quantity	1.24E+00	2.74E-01	4.53E+01	9.11E+01	-5.74E+01	-4.91E-01	-1.99E+00	-8.06E-01
	Note								
	Classification	Deduction	Deduction	Distribution	Distribution				
nsumables	Distribution	Plastics(kg)	Paper(kg)	Diesel truck: 10ton (kg•km)	Diesel truck: 4ton (kg•km)				
Cons	Quantity	-8.75E+00	-1.11E+01	1.10E+04	1.34E+04				
	Note								

6 Others

A.Product information:

All the parts mass per unit sorted by materials and by processes/assembly are included. The motor mass is included in ordinary steel.

B.Production site information:

The energy consumption & material use during the main body assemby and cartridge & toner shipment are included. The environmental impacts that are exhausted from the production site in the atmosphere and the water system are included.

C.Distribution stage information:

The total distance of the transportation in Japan of 100km is used according to PCR (AD-04) and the transportation overseas includes the transportation by track in China and by ship between China and Japan.

D. Product and accessories subject to this analysis: The power consumption is calculated assuming the use period of five years and 3,375,000 sheets printed during the use period according to the PCR (AD-04).

The toner consumption is summed up over the five years from the toner consumption data per sheet using our print pattern with 5% coverage.

The production impacts of the cartridges and toner used during the use period of five years are included. The impacts of the maintenance parts used and the transportation impacts of the maintenace during the use period of five years are included in this stage.

E. Disposal/Recycle information on the consumables and the maintenance parts during use stage:

The recycling information of the toner, the developer, the drums and the maintainance parts used during the use period of five years are included . The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus. Treatment of copper and deduction of copper include coper of "assembled circuit board". Incineration of assembled circuit board is included "Incineration: Industrial waste".

F.Disposal/Recycle stage information:

The information on the products recovered from users is included.

The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus. Treatment of copper and deduction of copper include copper of " assembled circuit board". Incineration of assembled circuit board is included "Incineration: Industrial waste".