



KONICA MINOLTA

CHROMA METER CR-400/410



CR-400

CR-410

The Standard in Measuring Color & Light

Giving Shape to Ideas

Introducing the successor to the Konica Minolta CR-300/310, our best-selling colorimeter globally accepted as the standard in a wide range of industries.

CR-400

Measurement area \varnothing 8mm

CR-410

Measurement area \varnothing 50mm



● The measuring head can perform measurement alone.

The measuring head is detachable from the data processor. Now, you can take measurements directly with the head alone. What's more, you can connect the measuring head directly to a PC. Simply install our optional software, and your PC can function as the data processor.

● User-defined evaluation formulas freely set up.

The CR-400 Series features a User Index function that allows you to configure the evaluation formula and color-calculation formula as desired. This feature is intended to meet the needs of color-control applications in which industry-specific or customized evaluation formulas are used instead of the versatile color system and standard evaluation formula such as $L^*a^*b^*$.

(Settings can be configured via a PC with optional software installed.)

Abundant accessories applicable to various materials.

A varied selection of accessories is available to accommodate various types of targets including powder, paste and opaque liquids.

● Compact data processor incorporates a high-speed printer.

The compact, lightweight data processor is battery-operated* and features a built-in high-speed printer. Its size and weight are approximately one-half those of the conventional DP-300 Series. In addition, the CR-400 Series is designed with a detachable shoulder strap for easier portability. *An AC adapter is included as a standard accessory.

Full data compatibility with the CR-300/310 series

To ensure data compatibility, the CR-400 Series utilizes the same illumination-viewing optical system as the conventional CR-300/310 Series. As a result, those upgrading from the preceding model can make full use of their existing data.

Easy-to-understand the name on the buttons, ensure smooth measurement and setting operations.

Achieves exceptional accuracy

Inter-instrument agreement : CR-400: ΔE^*ab within 0.6

CR-410: ΔE^*ab within 0.8

Repeatability : within ΔE^*ab 0.07

User calibration function ensures higher accuracy.

(Settings can be configured with the data processor or via a PC with optional software installed.)

● Color difference tolerance can be set to perform PASS/WARN/FAIL

(Settings can be configured with the data processor or via a PC with optional software installed.)

● Offers a wider range of color systems than the CR-300/310 Series.

● The measuring head alone can store up to 1,000 measurements. When the data processor is connected, up to 2,000 measurements can be stored.(The measuring head can store up to 100 color-difference target colors with or without the data processor connected.)

● Capable of displaying color-difference graphs that provide a visual representation of the color difference.

(When connected to data processor)

● A simple, cellular-phone-type text entry system is provided for entering the names of color-difference target colors and calibration channels.

(When connected to data processor)

● Features a large, easy-to-see LCD with a built-in backlight.

● The LCD offers six user-selectable languages for the display mode, including English and Japanese.

(When connected to data processor)

Can be powered with rechargeable batteries for reduced operating costs.


● Denotes a new feature not available with the previous CR-300/310 Series.

The CR-400/410 Series really shows its abilities in these applications.


When measuring powders or pastes



With the varied accessories, you can measure targets with diverse profiles.



Granular-Materials Attachment **CR-A50**



Glass Light-Projection Tube **CR-A33f** (For CR-400) **CR-A33e** (For CR-410)




When color control is performed with a customized evaluation formula, instead of the versatile color system



User-defined evaluation formulas can be entered as desired. Now, you can control color with customized evaluation formulas.

User index function
-Example-
Evaluation of tomato ripeness= $a^*/b^*+0.3a^*/L^*$



Note: The evaluation formula and grade indicated above are hypothetical examples used only to demonstrate the user index function.



When a compact colorimeter is needed in the field



The measuring head can be used independently of the data processor. This is advantageous when portability is required or limited space is available.




When measurements need to be printed on-site for labeling of samples



The compact data processor features a built-in printer for superior mobility.



System Diagram



Optional Accessories



Granular-Materials Attachment **CR-A50**

With the Granular-Materials Attachment CR-A50, the color of powders, pastes, grains, and other granular substances can be easily and accurately measured.




Glass Light-Projection Tube

CR-A33f (For CR-400) and **CR-A33e** (For CR-410)

Glass Light-Projection Tube CR-A33f and CR-A33e have a glass plate at the tip and can be used for measuring wet surfaces or for ensuring that materials such as textiles are flat during measurements.

SpectraMagic NX2

SpectraMagic NX2 is color management software that gives users a customizable screen display and a wide range of functions for operating and configuring their spectrophotometer or Chroma Meter from a computer. Users can display data lists and create color difference graphs and spectral graphs to assist in color management that requires judgment based on numerous values and indicators.




You can see the details in the catalog from the following 2D code. →



SpectraMagic NX2 web Site

CR-400 Utility Software **CR-S4w**

- To take measurements or change the measurement parameters of the CR-400/410 Series, you can control the unit with a PC.
- Measurement data can be transferred directly to a Microsoft Excel® file by means of the OLE function.
- Calibration data and color-difference reference color data can be uploaded or modified.



System requirements

- OS: Windows® 10 Pro 32-bit, 64-bit
Windows® 11 Pro
- The hardware of the computer system to be used must meet or exceed the greater of the recommended system requirements for the compatible OS being used or the following specifications.
- CPU: Pentium® 166MHz or higher
Memory: 32MB or higher
Hard disk: 100MB or more free space
Display resolution: VGA (640 × 480) or higher

- Windows® is a trademark or registered trademark of Microsoft Corporation in the USA and other countries.
- Pentium® is a trademark of Intel Corporation in the USA and other countries.
- Bluetooth® is a registered trademark of Bluetooth SIG, Inc. and is used under license agreement.

Specifications

Name	Chroma Meter Measuring Head	
Model	CR-400 Head	CR-410Head
Illumination/viewing system	Diffuse illumination/0° viewing angle (Specular component included/Conforms to JIS Z 8722 condition c standard.)	Wide-area illumination/0° viewing angle (Specular component included)
Detector	Silicone photo cells (6)	
Display range	Y: 0.01 to 160.00% (reflectance)	
Light source	Pulsed xenon lamp	
Measurement time	1 seconds.	
Minimum measurement interval	3 seconds.	
Battery performance	Approx. 800 measurements (when using batteries under company testing Konica Minolta's conditions)	
Measurement/illumination area	φ8/φ11	φ50/φ53
Repeatability	Within ΔE*ab0.07 standard deviation (when the white calibration plate is measured 30 times at intervals of 10 seconds)	
Inter-instrument agreement	ΔE*ab: within 0.6	ΔE*ab: within 0.8
Observer	Average of 12 BCRA series II colors	
Illuminant *1	C, D ₆₅	
Display *1	Chroma values, color difference values, PASS/WARN/FAIL display	
Tolerance judgment *1	Color difference tolerance (box tolerance and elliptical tolerance)	
Colorimetric data/indexes	XYZ, Y x y, L*a*b*, Hunter Lab, L*C*h, Munsell (only illuminant C), CMC(l:c), CIE1994, Lab99, LCh99, CIE2000, CIE Wl-Tw (only illuminant D ₆₅), WI ASTM E313 (only illuminant C), YI ASTM D1925 (only illuminant C), YI ASTM E313 (only illuminant C), User index (up to six can be registered from computer)	
Languages	Operating keys : English LCD : English (default) (LCD : German, French, Italian, Spanish, Japanese) *1	
Data memory	1,000 (measuring head and data processor save different data)	
Color difference target colors	100	
Calibration channels *1	20 channels (ch00 : white calibration, ch01 to ch19 : user calibration)	
Display	Dot-matrix LCD with back light (15 chars x 9 lines + 1 line for icon display)	
Interface	RS-232C compliant(for data processor/PC) USB 2.0 (When using USB-Serial Converter Cable (2 m) CR-A105) * Baud rate : 4800, 9600, 19200 (bps), set at 9600 bps when shipped from factory	
Power	4 AAA size alkaline or Ni-MH batteries, AC Adapter AC120V ~ 50/60 Hz (for N.America and Japan) AC230V ~ 50/60 Hz (for worldwide except N.America)	
Size (W x H x D)	102 x 217 x 63 mm	102 x 244 x 63 mm
Weight	Approx. 540g (including 4 AAA size batteries: not including RS-232C cable or USB cable)	
Operation temperature/humidity range	0 to 40°C, relative humidity 85% or less (at 35°C) with no condensation * Operating temperature/humidity range of products for North America : 5 to 40°C, relative humidity 80% or less (at 31°C) with no condensation	
Storage temperature/humidity range	-20 to 40°C, relative humidity 85% or less (at 35°C) with no condensation	
Other	LCD back light ON/OFF function (when ON, back light stays ON for 30 seconds after last key or measurement operation)	


*1 indicates when connected to the Data Processor or when not set using the Data Processor or the optional software, that some of the function are not available when the measuring head is not connected.

Name	Data Processor
Model	DP-400
Display range	Y : 0.01 to 160.00% (reflectance)
Measurement time *2	1 Seconds.
Minimum measurement interval *2	3 Seconds.
Battery performance	Approx. 800 measurements (when using batteries under company testing Konica Minolta's conditions)
Illuminant	C, D ₆₅
Display	Chroma values, color difference values, color difference graphs, PASS/WARN/FAIL display
Tolerance judgment *2	Color difference tolerance (box tolerance and elliptical tolerance) Only for the display function
Colorimetric data/indexes	XYZ, Y x y, L*a*b*, Hunter Lab, L*C*h, Munsell (only illuminant C), CMC (l:c), CIE1994, Lab99, LCh99, CIE2000, CIE Wl-Tw (only illuminant D ₆₅), WI ASTM E313 (only illuminant C), YI ASTM D1925 (only illuminant C), YI ASTM E313 (only illuminant C), User index (up to six registered in the Measuring Head can be used)
Languages	Operating keys : English, LCD : English (default), German, French, Italian, Spanish, Japanese
Data memory	Max. 2,000 pieces of data (divisible into 100 pages) Deletion and Undoing selected stored data (one piece of data or all data) are possible
Color difference target colors *2	Only for the operating function (100 pieces of data when the measuring head is connected; input of measurement values or numeric) (independent of page function)
Calibration channels *2	Only for the operating function (20 channels when the measuring head is connected) (ch00: white calibration; ch01 to ch19: user calibration)
Page function	100 pages
Display	Dot-matrix LCD with back light (16 chars x 9 lines + 1 line for icon display) Contrast adjustment
Printer	384 dot line thermal printer (can also print graphs) Automatically prints out all measurement results (can be set not to print)
Statistical function	Maximum, minimum, average, and standard deviation
Automatic measurement *2	Date and time display: year, month, day, hour, minute Timer: 3seconds. to 99 minutes. (Some measurement modes require more than 3 seconds.)
Interface	RS-232C compliant USB 2.0 (When using USB-Serial Converter Cable (2 m) CR-A105) Baud rate (bps): 19,200 fixed (when connected to PC) When measuring head is connected baud rate is automatically set to that of the measurement head
Power	4 AA size alkaline or Ni-MH batteries, AC Adapter AC120V ~ 50/60 Hz (for N.America and Japan) AC230V ~ 50/60 Hz (for worldwide except N.America)
Size (W x H x D)	100 x 73 x 255 mm
Weight	Approx. 600g (not including batteries, paper, cables)
Operation temperature/humidity range	0 to 40°C, relative humidity 85% or less (at 35°C) with no condensation * Operating temperature/humidity range of products for North America : 5 to 40°C, relative humidity 80% or less (at 31°C) with no condensation
Storage temperature/humidity range	-20 to 40°C, relative humidity 85% or less (at 35°C) with no condensation
Other	User calibration function (multi-calibration/manual calibration) *2, Measurements for automatic average function, Print ON/OFF function. CR-400 measurement data import function *2, All color space print ON/OFF function, Data protection ON/OFF function. Back light ON/OFF function. Buzzer ON/OFF function. Display color limit function, Remote mode (stored data output), Character input function (alphanumeric)


*2 indicates that part of or all functions are not available when the measurement head is not connected.

Dimensions (Units: mm)


Measuring Head **CR-400**



Measuring Head **CR-410**



Data Processor **DP-400**



Standard/Optional accessories

	Measuring Head CR-400	Measuring Head CR-410	Data Processor DP-400
Color Data Software			
SpectraMagic NX2	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
CR-400 Utility Software	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
CR-S4w	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
White Calibration Plate			
CR-A43	<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>
White Calibration Plate			
CR-A44	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
Protective Cap			
CR-A72	<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>
Protective Cap			
CR-A104	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
RS-232C Cable			
CR-A101(Head-DP)	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>
RS-232C Cable			
CR-A102(for PC)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
USB-Serial Converter Cable			
CR-A105(for PC)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
AC Adapter	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
Wrist Strap	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
CR-A73	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
Shoulder Strap			
SS-01			<input type="radio"/>
Hard Case			
CR-A103	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Roll Paper (one roll)			<input checked="" type="radio"/>
Roll Paper			
DP-A22(five rolls)			<input type="radio"/>
4 AA Size Batteries			<input checked="" type="radio"/>
4 AAA Size Batteries	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
Glass Light-Projection Tube			
CR-A33a/f	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Light-Projection Tube			
CR-A33c/d	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Glass Light-Projection Tube			
CR-A33e	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Granular-Materials Attachment	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
CR-A50	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Color Plates	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

● Standard accessory
○ Optional accessory

The specifications and appearance shown herein are subject to change without notice.

SAFETY PRECAUTIONS

For correct use and for your safety, be sure to read the instruction manual before using the instrument.

- Always connect the instrument to the specified power supply voltage. Improper connection may cause a fire or electric shock.
- Be sure to use the specified batteries. Using improper batteries may cause a fire or electric shock.

ISO Certifications of KONICA MINOLTA, Inc., Sakai Site

 <small>ISO 9001</small>	<small>ISO 9001</small> <small>Design, development, manufacture/ manufacturing management, calibration, and service of measuring instruments</small>	 <small>ISO 14001</small>
	<small>ISO 9001</small> <small>Design, development, manufacture/ manufacturing management, calibration, and service of measuring instruments</small>	

KONICA MINOLTA, INC.	Osaka, Japan	
Konica Minolta Sensing Americas, Inc.	New Jersey, U.S.A.	PHONE: (888)473-2656 (in USA), +1(201)236-4300 (outside USA) FAX: +1(201)785-2480 E-Mail: service.us@konicaminolta.com
Konica Minolta Sensing Europe B.V.	European HQ / BENELUX German Office French Office UK Office Italian Office Swiss Office Nordic Office Polish Office	Nieuwegein, Netherlands München, Germany Reissy CDG Cedex, France Warrington, United Kingdom Cinisello Balsamo, Italy Dietikon, Switzerland VÄSTRA FRÖLUNDA, Sweden Wrocław, Poland PHONE: +31(0)30 248-1193 PHONE: +49(0)89 4357 156 0 PHONE: +33(0)1 80 11 10 70 PHONE: +44(0)1925 467300 PHONE: +39 02849488.00 PHONE: +41(0)43 322-9800 PHONE: +46(0)31 7099464 PHONE: +48(0)71 73452-11 E-Mail: info.benelux@seu.konicaminolta.eu E-Mail: info.germany@seu.konicaminolta.eu E-Mail: info.france@seu.konicaminolta.eu E-Mail: info.uk@seu.konicaminolta.eu E-Mail: info.italy@seu.konicaminolta.eu E-Mail: info.switzerland@seu.konicaminolta.eu E-Mail: info.nordic@seu.konicaminolta.eu E-Mail: info.poland@seu.konicaminolta.eu
Konica Minolta (CHINA) Investment Ltd.	SE Sales Division Beijing Office Guangzhou Office Chongqing Office Qingdao Office Wuhan Office Shenzhen Office Xi'an Office Xiamen Office	Shanghai, China Beijing, China Guangzhou, China Chongqing, China Shandong, China Hubei, China Shenzhen, China Xi'an, China Xiamen, China PHONE: +86-(0)21-6057-1089 PHONE: +86-(0)10-8522 1551 PHONE: +86-(0)20-3826 4220 PHONE: +86-(0)23-6773 4988 PHONE: +86-(0)532-8079 1871 PHONE: +86-(0)27-6885 0586 PHONE: +86-(0)755-2868 7535 PHONE: +86-(0)592-7107 399 PHONE: +65 6563-5533 E-Mail: hcn_sensing@gcp.konicaminolta.com E-Mail: hcn_sensing@gcp.konicaminolta.com E-Mail: hcn_sensing@gcp.konicaminolta.com E-Mail: hcn_sensing@gcp.konicaminolta.com E-Mail: hcn_sensing@gcp.konicaminolta.com E-Mail: hcn_sensing@gcp.konicaminolta.com E-Mail: hcn_sensing@gcp.konicaminolta.com E-Mail: hcn_sensing@gcp.konicaminolta.com E-Mail: hcn_sensing@gcp.konicaminolta.com E-Mail: hcn_sensing@gcp.konicaminolta.com
Konica Minolta Sensing Singapore Pte. Ltd.	Singapore	PHONE: +65 6563-5533 E-Mail: se-service.sg@konicaminolta.com
Konica Minolta Sensing Korea Co., Ltd.	Korean HQ Cheonan Office	Goyang-si, Korea Cheonan-si, Korea PHONE: +82(0)2-523-9726 PHONE: +82(0)41-556-9726 E-Mail: se.korea@konicaminolta.com E-Mail: se.korea@konicaminolta.com