

Page:1/7

MSDS No.: PRT-3032

Product Name: DEVELOPER (BLACK)

Prepared Date: 20-Feb-2006 Revised Date: 4-Jan-2016

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name: DEVELOPER (BLACK) used for: magicolor7440series/7450series

Supplier Identification:

Konica Minolta Business Solutions (Canada), Ltd. 369 Britannia Road East Mississauga, Ontario L4Z 2H5 Telephone: (905)890-6600 Facsimile: (905)283-2511

Emergency Telephone No. CHEMTREC Telephone: 1-800-424-9300 WHMIS: This product is NOT subject to the controlled products regulations.

2. HAZARDS IDENTIFICATION

Regulation (EC) No 1272/2008

Classification: Not classified as dangerous.

Hazard Communication Standard (USA)

Classification: Not classified as dangerous.

LABEL ELEMENTS

Precautionary pictograms:	
Signal word:	
Hazard Statement:	
Precautionary Statements:	

Other Hazards

Dust explosion (like most finely divided organic powders).



MSDS No.: PRT-3032

Prepared Date: 20-Feb-2006 Revised Date: 4-Jan-2016 3. COMPOSITION / INFORMATION ON INGREDIENTS Substance [] Preparation [X] Major Ingredients: [Generic Name] [CAS No.] [%] Ferrite Iron oxide 1309-37-1 60-70 . Manganese oxide 1344-43-0 15-25 . Magnesium oxide 1309-48-4 1-10 Styrene-acrylic resin +++ 1-10
3. COMPOSITION / INFORMATION ON INGREDIENTS Substance [] Preparation [X] Major Ingredients: [Generic Name] [CAS No.] [%] Ferrite Iron oxide 1309-37-1 60-70 . Manganese oxide 1344-43-0 15-25 . Magnesium oxide 1309-48-4 1-10 Styrene-acrylic resin +++ 1-10
Substance [] Preparation [X] Major Ingredients: [Generic Name] [Generic Name] [CAS No.] [%] Ferrite Iron oxide 1309-37-1 60-70 . Manganese oxide 1344-43-0 15-25 . Magnesium oxide 1309-48-4 1-10 Styrene-acrylic resin +++ 1-10
Major Ingredients:[CAS No.][%][Generic Name][CAS No.][%]FerriteIron oxide1309-37-160-70.Manganese oxide1344-43-015-25.Magnesium oxide1309-48-41-10Styrene-acrylic resin+++1-10
[Generic Name] [CAS No.] [%] Ferrite Iron oxide 1309-37-1 60-70 . Manganese oxide 1344-43-0 15-25 . Magnesium oxide 1309-48-4 1-10 Styrene-acrylic resin +++ 1-10
[Generic Name] [CAS No.] [%] Ferrite Iron oxide 1309-37-1 60-70 . Manganese oxide 1344-43-0 15-25 . Magnesium oxide 1309-48-4 1-10 Styrene-acrylic resin +++ 1-10
Ferrite Iron oxide 1309-37-1 60-70 Manganese oxide 1344-43-0 15-25 Magnesium oxide 1309-48-4 1-10 Styrene-acrylic resin +++ 1-10
.Manganese oxide1344-43-015-25.Magnesium oxide1309-48-41-10Styrene-acrylic resin+++1-10
. Magnesium oxide 1309-48-4 1-10 Styrene-acrylic resin +++ 1-10
Styrene-acrylic resin +++ 1-10
Acryl resin +++ 1-10
Carbon black 1333-86-4 < 1
+++: Supplier's confidential information
Hazardous Ingredients:
Chemical Name: Carbon black
CAS No.: 1333-86-4
EINECS-No.: 215-609-9 REACH Registration number: 01-2119384822-32-XXXX
NTP(USA): Not listed IARC Monographs: Group 2B
California Proposition 65(USA): Listed
Symbol(EC): Not listed H code(EC): Not listed
DFG-MAK(GER): III 3B
Chemical Name: Manganese oxide
CAS No.: 1344-43-0 EINECS-No.: 215-695-8
Symbol(EC): Not listed H code(EC): Not listed
4. FIRST-AID MEASURES
Ingestion: Wash out mouth with water. Drink one or two glasses of water. If symptoms occur, get medical
attention.
Inhalation: Move victim to fresh air immediately. If symptoms occur, get medical attention.
Eye Contact: Immediately flush eyes with plenty of water for 15 minutes. If symptoms occur, get medical
attention.

Skin Contact: Wash with water and mild soap.

5. FIRE-FIGHTING MEASURES

 Suitable Extinguishing Media: CO2, water spray, foam and dry chemical

 Extinguishing Media to Avoid: Full water jet

 Fire and Explosion Hazards: If dispersed in air, like most finely divided organic powders, may form an explosive mixture.

 Protection of Firefighters:
 Use self-contained breathing apparatus(SCBA).



MSDS No.: PRT-3032

Product Name: DEVELOPER (BLACK)

Prepared Date: 20-Feb-2006 Revised Date: 4-Jan-2016

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: None

Environmental Precautions: None

Methods for Cleaning Up: Wear personal protective equipment(See Section 8). Vacuum or sweep material and place in a bag and hold for waste disposal. Use vacuum equipped with High Efficiency Particulate Air(HEPA) filter. Vacuum should be electrically bonded and grounded to dispel static electricity. To avoid dust generation, do not sweep dry.

7. HANDLING AND STORAGE

Handling

Technical Measures:NonePrecautions:Do not breathe dust. Avoid contact with eyes.Safe Handling Advice:Try not to disperse the particulates.StorageTechnical Measures:NoneStorage Conditions:Storage Conditions:Keep container closed. Store in a cool and dry place. Keep out of reach of children.Incompatible Products:NonePackaging Materials:Bottles or Cartridge designated by Konica

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures Ventilation: None required with intended use. Control Parameters (As total dust) ACGIH-TLV (USA): 10mg/m3 (Inhalable particles), 3.0 mg/m3 (Respirable particles) OSHA-PEL (USA): 15mg/m3 (Total dusts), 5.0 mg/m3 (Respirable fraction) DFG-MAK (GER): 4mg/m3 (Inhalable fraction), 1.5mg/m3 (Respirable fraction) Safe Work Australia-TWA: 10mg/m3 Control Parameters (As Ingredients: Carbon black) ACGIH-TLV (USA): 3mg/m3 OSHA Z-Table (USA): 3.5mg/m3 Safe Work Australia-TWA: 3mg/m3 Control Parameters (As Ingredients: Manganese oxide) ACGIH-TLV(USA): 0.1mg/m3(Mn;Inharable Fraction) 0.02mg/m3(Mn;Respirable Fraction) OSHA Z-Tables(USA):ceiling 5mg/m3 Safe Work Australia-TWA: 1mg/m3(Mn) Personal Protective Equipment Not required under normal conditions. For use other than in normal operating procedures (such as in the event of large spill), goggles and respirators may be required. Hygiene Measures: Wash hands after handling.



SAFETY DATA SHEET

Page:4/7

MSDS No.: PRT-3032

Product Name: DEVELOPER (BLACK)

Prepared Date: 20-Feb-2006 Revised Date: 4-Jan-2016

9. PHYSICAL AND CHEMICAL PROPERTIES Appearance Physical State: Solid Color: Black

Physical State: Solid	Color: Black
Form: Powder (mean dia. is 30um by volume)	
Odor:	Almost odorless
PH	Not applicable
Boiling Point(°C):	Not applicable
Melting Point(°C)/[F]:	Around 125 /[257] (Softening Point)
Flash Point(°C):	Not applicable
Auto-Ignition Temperature(°C):	No data available
Upper/ lower flammability or explosive limits	No data available
Explosion Properties:	
Evaporation rate:	No data available
Vapor Pressure:	Not applicable
Vapor density:	Not applicable
Specific Gravity:	5.0
Solubility:	Insoluble in water.
Partition Coefficient, n-Octanol/Water:	Not applicable
Decomposition temperature:	Not applicable

10. STABILITY AND REACTIVITY

Reactivity:	None.	
Stability:	Stable except above 200C(392F).	
Hazardous Reactions:	Dust explosion, like most finely divided organic powders.	
Conditions to avoid:	Electric discharge, throwing into fire.	
Materials to Avoid:	Oxidizing materials.	
Hazardous Decomposition Products: CO, CO2, and smoke.		
Hazardous Polymerization:	Will not occur.	



SAFETY DATA SHEET

MSDS No.: PRT-3032

Product Name: DEVELOPER (BLACK)

Prepared Date: 20-Feb-2006 Revised Date: 4-Jan-2016

11. TOXICOLOGICAL INFORMATION

Acute Toxicity:

Ingestion(oral), LD50(mg/kg):	>2500(Rat) *	
Dermal, LD50(mg/kg):	No data available	
Inhalation, LC50(mg/l):	No data available	
(This was the highest attain	able concentration.)	
Eye irritation:	No data available	
Skin irritation:	Mild irritant(Rabbit) *	
Skin sensitizer:	Non sensitizer * (Guinea-Pig) *	
Local Effects: see Chronic Toxicity or Long term Toxicity		

Chronic Toxicity or Long Term Toxicity:

In a two-year inhalation study of chronic toxicity and carcinogenicity using a typical toner in rats, there were no lung changes at all in the lowest exposure level (1mg/m3), the most relevant level to potential human exposures. A minimal to mild degree of fibrosis was noted in 22% of the animals at the middle exposure level (4mg/m3), and a mild to moderate degree of fibrosis was observed in 92% of the rats at the highest exposure level(16mg/m3). The lung changes observed in the higher exposure groups are interpreted in terms of "lung overloading", a series of generic responses to the presence of large guantities of respirable, insoluble and relatively benign dusts retained for extended time periods in the lungs. Lung tumor frequency was unchanged among rats exposed to toner at the three exposure levels, and for air-only control rats.

Carcinogenicity

The IARC reevaluated carbon black as a Group 2B carcinogen (possible human carcinogen). This evaluation is given to Carbon Black for which there is inadequate human evidence, but sufficient animal evidence. The latter is based upon the development of lung tumors in rats receiving chronic inhalation exposures to free carbon black at levels that induce particle overload of the lung.

Studies performed in animal models other than rats have not demonstrated an association between carbon black and lung tumors. Moreover, a two-year cancer bioassay using a typical toner preparation containing carbon black demonstrated no association between toner exposure and tumor development in rats.

Mutagenicity: Negative *(AMES test) Teratogenicity: No data available (*= Based on data for other Konica Minolta Products with similar ingredients)

12. ECOLOGICAL INFORMATION

No data are available on the adverse effects of this material on the environment.

Ecotoxicity: No data available No data available Mobility: Persistence and degradability: No data available Bioaccumulative potential: No data available

13. DISPOSAL CONSIDERATION

When disposing of the waste or recovered material, consult federal, state and/or local regulations for the proper disposal method.



MSDS No.: PRT-3032

Product Name: DEVELOPER (BLACK)

Prepared Date: 20-Feb-2006 Revised Date: 4-Jan-2016

14. TRANSPORT INFORMATION

Information on Code and Classifications According to International Regulations UN Classification: None Further information: Not a dangerous good under IATA or IMDG. Hazchem code (Austl.): None

15. REGULATORY INFORMATION

US Information

TSCA (Toxic Substances Control Act):

All chemical substances in this product comply with all applicable rules or order under TSCA.

California Proposition 65:

Ingredient carbon black subject to California Proposition 65 is bound in polymer-matrices so that warnings are not required.

CERCLA(Comprehensive Environmental Response Compensation and Liability Act) :

None.

SARA Title III (Superfund Amendments and Reauthorization Act) 302 Extreme Hazardous Substance : None.

311/312 Hazard Categories :

None.

313 Reportable Ingredients :

None.

EU Information

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

• Regulation (EC) No 2037/2000 of the European Parliament and of the Council on Substances That Deplete the Ozone Layer: Not applicable

• Regulation (EC) No 850/2004 of the European Parliament and of the Council on Persistent Organic Pollutants and Amending Directive 79/117/EEC (POPs): Not applicable

• Regulation (EU) No 649/2012 of the European Parliament and of the Council on Concerning the Export and Import of Dangerous Chemicals (PIC): Not applicable

• Directive 2012/18/EU of the European Parliament and of the Council on the Control of Major-Accident Hazards Involving Dangerous Substances, Amending and Subsequently Repealing Council Directive 96/82/EC, (Seveso III): Not applicable

• Regulation (EC) No 1907/2006 of the European Parliament and of the Council:

- Annex XIV- List of Substances Subject To Authorization: Not applicable
- Annex XVII- Restrictions on the Manufacture, Placing on the Market and Use of Certain Dangerous Substances, Preparations and Articles: Not applicable

For this product a chemical safety assessment was not carried out.



Page:7/7

MSDS No.: PRT-3032

Product Name: DEVELOPER (BLACK)

Prepared Date: 20-Feb-2006 Revised Date: 4-Jan-2016

16. OTHER INFORMATION

HMIS Rating: The National Paint and Coating Association (USA): Health: 1 Flammability: 1 Reactivity: 0 Explanation of term: IARC 2B means "possible human carcinogen". Abbreviations: ACGIH-TWA: Threshold Limit Value of American Conference of Government Industrial Hygienists CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act DFG-MAK: Maximale Arbeitsplatz-Konzentration by Deutsche Forschuugsgemeinschaft DGR: Dangerous Goods Regulations EINECS: European Inventory of Existing Commercial Chemical Substances H-Code: Hazard Code HMIS: Hazardous Materials Identification System IARC: International Agency for Research on Cancer IATA: International Air Transport Association IMDG: International Maritime Dangerous Goods Code NTP: National Toxicology Program **OEL:** Occupational exposure limit OSHA: Occupational Safety and Health Administration PBT: Persistent, Bioaccumulative and Toxic SARA: Superfund Amendments and Reauthorization Act TSCA: Toxic Substances Control Act vPvB: very Persistent and very Bioaccumulative Revision Information: Regular revision on revised date. Literature References: ANSI Z400.1-1993 ISO 11014-1 Commission Directive 91/155/EEC IARC(2010): IARC monographs on the Evaluation of the Carcinogenic Risk of Chemicals to Humans, Vol. 93, Carbon Black, Titanium Dioxide, and Talc, Lyon, pp. 43-191 H.Muhle, B.Bellmann, O.Creutzenberg, C.Dasenbrock, H.Ernst, R.Kilpper, J.C.MacKenzie, P.Morrow, U.Mohr, S.Takenaka, and R.Mermelstein(1991) Pulmonary Response to Toner upon Chronic Inhalation Exposure in Rats. Fundamental and Applied Toxicology 17, pp.280-299. Restrictions: The above information is believed to be accurate and represents the best information currently available to

Our Corporation. However, Our Corporation makes no warranty with respect to such information, and Our Corporation assumes no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes.