Product Environmental Aspects Declaration

製品環境情報 http://www.jemai.or.jp

EP and IJ printer (PCR-ID:AD-04)

No. AD-18-1086 Date of publication Nov./1/2018



http://konicaminolta.jp

Please direct any inquiries or comments to e-mail: bt-environ@pub.konicaminolta.jp



Marking technologies Electrophotographic Printer (EP)

Printing speed 81 prints-per-minute(B/W), 81 prints-per-minute(color)

Maximum copy paper A3

Duplex printing Non-stack ADU equipped

Life Cycle Impact

Consumption and discharge in a life cycle	All the stage sum totals
Global warming(CO ₂ equivalent):kg	4,590 (3,924)
Acidification(SO₂equivalent):kg	7.6 (6.2)
Energy resources(crude oil equivalent):MJ	86,309 (75,331)

※Figures in()indicated environmental impact including recycle effect *note3


Warming load CO₂ equivalent of each stage (kg)



Total of 3,936,600 sheets on the assumption of five years usage.

Environmental impact by copypaper is not included.

*The picture is attached with options.



Notes:

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at http://www.ecoleaf-jemai.jp/eng/ for details.
- 3. Recycle Effect illustrates an indirect influence to other products/services.
- 4. Basic Units used for calculations are based on Japan domestic data at this time, due to a lack of base data to establish localized Basic Unit for overseas locations adequately.

[Supplemental environmental information]

- Certified Environmental Standards
 - International Energy Star Program
- Conforming to Japanese Law on Promoting Green Purchasing


PCR review was conducted by : PCR Deliberation Committee, January 01,2008, Name of reprentative : Youji Uchiyama, University of Tsukuba, Graduate School

Independent verification of the declaration and data, according to ISO14025 □internal ■external Third party verifier: The third party verifier *: Kazuo Naito

Programme operator: Japan Environmental Management Association for Industry, ecoleaf@jemai.or.jp

^{*} In the case of an business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

Product Environmental Information Data Sheet (PEIDS)





PORT	PCR name				EP and IJ printer		Product type AccuiroPress C83hc						
Part	PCR-ID)	AD-04		Product weight[kg]	312.0	Package[kg]	42.7	Weight total[kg]	354.7	
Part	, ,						Produ	ıction					
The control	In/Out items				Life Gycle Stage	Unit			Distribution	Use	Disposal	Recycle	
Coal New Coa	, 0	ut ito				M.I			7.26E±02	6.01E+04	1 96F+02	-1 10E+04	
Martin County No. No.			Ene	ergy Co	onsumption								
Part		1			Coal								
Natural Gas													
Management Man			E	nerav	, ,								
Management of the Purpose of the P													
Managements No. No			_			IIIg	2.04E-03	Z.83E-03	1.136-07	1.23E-02	3.63E-03	-4.90E-04	
Montange Management Manag						kg	3.57E+01	0	0	2.69E+02	0	_4 02E±01	
Management Man					• ,	le or	2 425+02	0	0	1 255±02	0		
Month Part													
Mickel one Natural South					* *								
Value Valu		ng t	<u>e</u> "										
Value Valu		umpt	urces										
Value Valu		onsu	xhau										
Value Valu		rce C	ш –	/laterial									
Value Valu		sour om tl	IV	паста									
Silver ore		Re											
Silve rore													
Silica sand kg 4.70E+00 0 0 1.35E+00 0 -1.16E+00 Rock salt kg 2.05E+01 2.68E-02 0 2.73E+00 1.24E-01 -8.65E+00 -7.85E-01 -2.29E+01 7.38E-01 -2.29E+01 7.39E-01 -2.29E+01 7.29E-02 -2.29E+01 -2.29E-02 -2.29E+01 7.29E-02 -2.29E+01 -2.29E-02													
Rock sait Na 2.05E+01 2.68E+02 0 2.73E+00 1.24E+01 -8.65E+00 0 0 0.254E+01 7.38E-01 -2.29E+01 -2.2							, ,						
Limestone Rg 4.62E+01 0 0 2.54E+01 7.38E-01 -2.29E+01													
Solution Solution	es												
Solution Solution	alys												
Solution Solution	ry an												
Solution Solution	ento							•					
SOX kg 1.08E+00 2.50E-01 2.79E-02 2.35E+00 4.32E-02 -7.59E-01	N.												
Nox kg 1.34E+00 2.04E-01 1.84E-01 3.58E+00 1.26E-01 -8.50E-01 N2O kg 8.26E-02 6.74E-03 9.50E-03 3.96E-01 2.09E-04 -5.24E-02 CH4 kg 6.57E-03 7.60E-03 3.07E-07 3.25E-02 1.57E-04 -1.12E-03 CO kg 2.57E-01 4.88E-02 3.64E-02 5.58E-01 3.17E-02 -1.82E-01 NNVOC kg 1.28E-02 1.49E-02 6.01E-07 6.36E-02 3.07E-04 -2.18E-03 CXHy kg 4.08E-02 1.33E-03 6.43E-03 1.13E-01 1.13E-03 -2.57E-02 Use of the complex of the comple													
N2O Rg S.26E-02 6.74E-03 9.50E-03 3.96E-01 2.09E-04 -5.24E-02													
The following state The following state			to Atmosphere										
The folian The													
NMVOC kg 1.28E-02 1.49E-02 6.01E-07 6.36E-02 3.07E-04 -2.18E-03													
Second Company Compa													
Hard		•											
P total kg		nent			•								
P total kg		Disch						1.08E=02	1.91E-02	3.33E-01	7.89E-03	-1.26E-01	
P total kg		ion/[-	_	-	_	_	_	
P total kg		miss o the	40 184-4				_	_	_	-	_	_	
SS kg - - - - - - - -		ш	to water	system									
To Soil system Unspecified solid waste kg 6.70E+00 1.73E-01 0 1.60E+02 1.54E+02 -5.06E+00							_					-	
Slag kg 7.55E+01 0 0 4.60E+01 0 -4.71E+01												-	
Soli system Sludge kg 2.06E+01 0 0 2.33E+01 0 -1.75E+01					· ·								
Low emission radioactive waste kg 1.78E-03 1.99E-03 8.02E-08 8.56E-03 4.09E-05 -3.48E-04			4- 6 "										
Tadioactive waste kg 1.78E-03 1.99E-03 8.02E-08 8.06E-03 4.09E-05 -3.48E-04			to Soil s	ystem	_	kg	2.06E+01	U	U	2.33E+01	U	−1./5E+01	
Table Tabl						kg	1.78E-03	1.99E-03	8.02E-08	8.56E-03	4.09E-05	-3.48E-04	
Tesources Teso													
Tesources Teso		nptior				kg	3.67E+02	1.24E+02	1.61E+01	9.13E+02	3.97E+00	-1.89E+02	
Tesources Teso		unsuo	Exhau	ıstible									
To Soil To S		rce C				kg	4.87E+03	0	0	9.92E+03	0	-5.81E+03	
To Soil To S	ııt	Seson			(iron ore equivalent)						,		
to Water system to Soil	me												
to Water system to Soil	ses	ion				kg	1.25E+03	3.32E+02	5.41E+01	2.88E+03	7.80E+01	-6.67E+02	
to Water system to Soil	as	mpt			Acidification	kø				4 86F+00			
to Water system to Soil	act	nsu	Atmos	pnere	(SO2 equivalent)	8	2.002.00	0.02E 01	1.072 01	4.00E 100	I.OZE OI	1.002.00	
to Water system to Soil	m	ပိ											
		on											
		nisi	_										
n system													
		þ	sys	tem									

[Notes for readers: EcoLeaf common rules]

I. Stage related

- A. "Production" stage is intended for two sub-stages listed below.
 - (1) "Raw material" production: consists of mining, transportation and raw material production.
 - (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal/recycle of consumables /maintenance goods (e.g. replacement parts).
- D. "Disposition/Recycle" stage is intended for environmental impacts by product disposition/recycle, and deduction by recycling (e.g. impact reduction of raw material production).
- E. "Recycle Effect" illustrates an indirect environmental influences to other products/services by use of reclaimed materials/parts, and/or by supply of used products to other businesses for material reclaim/parts reuse.
- Case 1: Use of reclaimed materials/parts: Sum of increase of environmental impact by collection activities of used materials/parts, and decrease by volume reduction of used materials/parts.
- Case 2: Supply of used products to other businesses for material reclaim/parts reuse: Sum of increase of environmental impact by materials/parts reclaiming process, and decrease by volume reduction of new materials/parts production.

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.
- B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III Impact analyses

- Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO2 in case of "Global Warming").
- A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.
- B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

IV Data entry format


- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.
- C. Indicate "-" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
 - (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

- A."Raw material" in "Production" includes environmental impacts generated during mining transportation material production phases of the main body of the printer and the toner cartridge enclosed in the printer. The environmental impacts are calculated using the eco-leaf basic unit DB for calculations.
- B. "Product" in "production" includes environmental impacts of processing of the parts (injection, blow-, press- and glass-molding).

 The environmental impacts from the parts assembly plant which is different from the main body assembly plant (such parts are clacified in "parts C") are
 - The environmental impacts from the parts assembly plant which is different from the main body assembly plant (such parts are clacified in "parts C") are calculated using the eco-leaf basic unit DB for calculations.
 - The impacts from the main body assembly plant are calculated using the quantitative data on environmental impacts in our assembly plant.
- C. Regarding the basis and the basic units for calculations during distribution stages
- The total distance of the transportation in Japan of 100km is used according to PCR (AD-04) and the transportation overseas includes the transportation by track in China and by ship between China and Japan.
- D. Regarding the basis and the basic units for calculations during use and consumption stage
- The power consumption is measured by the TEC test procedure according to PCR (AD-04). 3,936,600 sheets are printed in total during the use period of five years.
- The toner consumption is summed up over the five years from the toner consumption data per sheet using our print pattern with 5% coverage.
- The production loads and the collection & recycling impacts of the toner cartridges used over the five years are included in this stage.
- E. The recycling impacts are calculated assuming that 40% of the end-of-life printers are recovered from users according to PCR (AD-04). The impacts are calculated with the remaining 60% following the disposal senario as general wastes.
- F. The impacts of materilal production of recycled materials are included in the values with minus as a recycling effect.

Product data sheet





PCR name	EP and IJ printer (PCR-ID:AD-04)	Product type		AccuiroP	ress C83hc		
_ LCA/LCIA in units of:	1	Product weight[kg]	312.0	Package[kg]	42.7	Weight total[kg]	354.7

1. Product information (per unit): parts etc. by material and by process/assembly method

	Breakdown of primar		Math breakdown of par	rts, which need to apply	Processing / Assembly	Base Units (Parts B, C)	
Material name Weight (kg)		Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
Ordinary steel	2.23E+02	Rubber	8.59E-01	Press molding:Iron	2.35E+02		
Stainless steel	2.98E+01	Semiconductor circuit board	4.71E+00	Press molding:Nonfe rrous metal	1.23E+01		
Aluminium	9.07E+00			Injection molding	3.90E+01		
Other metals	3.27E+00						
Glass	8.17E-01						
Thermoplastic resin	4.35E+01						
Wood	1.65E+01						
Paper	2.32E+01						
Subtotal	3.49E+02	Subtotal	5.57E+00				
	Total		3.55E+02	Subtotal	2.86E+02	Subtotal	

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site. SOx and NOx should be indicated in SO2, NO2 equivalent.

c	Classification	Energy	Energy	Material	Material				
Consumption	Distribution	Electricity	Furnace urban	Industrial	Groundwater				
	Distribution	(kWh)	gas (m³)	water(kg)	(kg)				
	Quantity	4.26E+02	1.13E+00	4.59E+03	7.16E+01				
0	Note								
	Classification	To Water							
Emission/ Discharge	Classification	system							
rissi	Distribution	Sewage (kg)							
En	Quantity	4.61E+03							
	Note								
3. Distribu	ution stage information (per unit	: means, distan	ce, loading ratio	, consumptions	and emissions/	discharges.			
	Means of transportation	Freight by	Freight by	Freight by	Freight by	Diesel truck	Diesel truck	Diesel truck	Diesel truck
		ship	ship	ship	ship	:20ton	:20ton	:20ton	:20ton
	Conditions	Load(kg•km)	Weight (kg)	Distance (km)	Loading Ratio(%w)	Load(kg•km)	Weight (kg)	Distance (km)	Loading Ratio(%w)
S	Quantity	8.87E+05	3.55E+02	2.50E+03	1.00E+02	8.30E+04	3.55E+02	1.99E+02	8.51E+01
) JE	Note								
Distribution	Means of transportation	Diesel truck	Diesel truck	Diesel truck	Diesel truck				
٥	ividaris of transportation	:2ton	:2ton	:2ton	:2ton				
	Conditions	Load(kg•km)	Weight (kg)	Distance (km)	Loading Ratio(%w)				
	Quantity	1.50E+03	3.55E+02	7.50E-01	1.77E+01				
	Note								

Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.
 1 Product and accessories subject to this analysis

Product	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Electricity	Gasoline as	Furnace urban	Industrial	Groundwater	Ordinary steel	Stainless steel	Aluminium
	Distribution	(kWh)	fuel(kg)	gas (m³)	water(kg)	(kg)	(kg)	(kg)	(kg)
	Quantity	2.71E+03	1.63E+00	8.28E+01	2.37E+03	1.06E+04	9.62E+01	7.69E+01	1.03E+01
	Note								
	Classification	Consumption	Consumption	Consumption	Processing	Processing	Processing	Processing	
Product	Distribution	Thermoplastic resin(kg)	Paper(kg)	Rubber(kg)	Press:Iron (kg)	Press: Nonferrous(kg	Injection molding(kg)	Blow molding (kg)	
_	Quantity	2.70E+02	4.93E+00	1.26E+00	1.43E+02	6.69E+00	3.92E+01	4.51E+01	
	Note								
	Classification	Assembly	To Water system						
Product	Distribution	Parts assembly(kg)	Sewage (kg)						
_	Quantity	4.51E+01	1.03E+04						
	Note								
	Classification	Distribution	Distribution	Distribution					
Product	Distribution	Freight by ship (kg·km)	Diesel truck: 20ton (kg•km)	Diesel truck: 10ton (kg•km)					
	Quantity	2.27E+03	5.67E+02	4.83E+04					
	Note								
:	141 /0 1 1 1 / 41								

4.2 Dispo	sition/Recycle information on c	onsumables and	l replacement pa	irts					
	Classification	Consumption	Consumption	Treatment	Treatment	Treatment	Treatment	Treatment	Treatment
Consumables	Distribution	Electricity (kWh)	Kerosene(kg)	Recycle: to iron(kg)	Recycle: to Aluminum(kg)	Recycle: to copper(kg)	Recycle: to plastics(kg)	Recycle: to Paper(kg)	Industrial waste destruction by fire(kg)
0	Quantity	6.24E+00	2.22E-01	6.93E+01	4.10E+00	5.30E-02	3.62E+01	2.34E+00	5.05E-01
	Note								
	Classification	Treatment	Treatment	Treatment	Deduction	Deduction	Deduction	Deduction	Deduction
Consumables	Distribution	Industrial waste inning(kg)	Waste destruction by fire(kg)	Waste inning(kg)	Iron(kg)	Aluminum(kg)	Copper(kg)	Plastics(kg)	Paper(kg)
8	Quantity	3.66E-01	5.92E+01	1.43E+02	-6.93E+01	-4.10E+00	-5.30E-02	-3.62E+01	-2.34E+00
	Note								
	Classification	Distribution	Distribution						
Consumables	Distribution	Diesel truck: 10ton (kg*km)	Diesel truck: 4ton (kg•km)						
ő	Quantity	1.62E+04	1.96E+04						
	Note								

5. Disposition/Recycle stage information (per product): process method and scenarios

s,	Classification	Consumption	Consumption	Treatment	Treatment	Treatment	Treatment	Treatment	Treatment
Consumables	Distribution	Electricity (kWh)	Kerosene(kg)	Recycle: to iron(kg)	Recycle: to Aluminum(kg)	Recycle: to copper(kg)	Recycle: to Glass(kg)	Recycle: to plastics(kg)	Recycle: to Paper(kg)
Suo	Quantity	6.61E+00	2.35E-01	1.02E+02	3.63E+00	1.95E+00	3.27E-01	1.72E+01	1.65E+01
0	Note								
	Classification	Treatment	Treatment	Treatment	Treatment	Deduction	Deduction	Deduction	Deduction
Consumables	Distribution	Incineration: Industrial waste(kg)	Landfill: Industrial waste(kg)	Incineration to landfill (as ash)(kg)	Landfill: General waste(kg)	Iron(kg)	Aluminium (kg)	copper(kg)	Glass(kg)
Ö	Quantity	1.49E+00	4.49E-01	5.05E+01	1.46E+02	-1.02E+02	-3.63E+00	-1.95E+00	-3.27E-01
	Note								
	Classification	Deduction	Deduction	Distribution	Distribution				
Consumables	Distribution	Plastics(kg)	Paper(kg)	Diesel truck: 10ton (kg•km)	Diesel truck: 4ton (kg•km)				
Š	Quantity	-1.72E+01	-1.65E+01	1.71E+04	2.07E+04				
	Note								

6. Others

A.Product information:

All the parts mass per unit sorted by materials and by processes/assembly are included. The motor mass is included in ordinary steel.

The energy consumption & material use during the main body assemby and cartridge & toner shipment are included. The environmental impacts that are exhausted from the production site in the atmosphere and the water system are included.

C.Distribution stage information:

The total distance of the transportation in Japan of 100km is used according to PCR (AD-04) and the transportation overseas includes the transportation by track in China and by ship between China and Japan.

D. Product and accessories subject to this analysis:
The power consumption is calculated assuming the use period of five years and 3,936,600 sheets printed during the use period

according to the PCR (AD-04).

The toner consumption is summed up over the five years from the toner consumption data per sheet using our print pattern with 5%

coverage.

The production impacts of the cartridges and toner used during the use period of five years are included.

The impacts of the maintenance parts used and the transportation impacts of the maintenance during the use period of five years are included in this stage.

E. Disposal/Recycle information on the consumables and the maintenance parts during use stage:

The recycling information of the toner, the developer, the drums and the maintainance parts used during the use period of five years

are included .

The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus.

Treatment of copper and deduction of copper include copper of " assembled circuit board" . Incineration of assembled circuit board is included "Incineration: Industrial waste".

F.Disposal/Recycle stage information:
The information on the products recovered from users is included.

The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus. Treatment of copper and deduction of copper include copper of " assembled circuit board". Incineration of assembled circuit board is included "Incineration: Industrial waste".