


PCR review was conducted by : PCR Deliberation Committee, January 01,2008, Name of reprentative : Youji Uchiyama, University of Tsukuba, Graduate School

Independent verification of the declaration and data, according to ISO14025 □internal ■external Third party verifier: The third party verifier * : Kazuo Naito

Programme operator: Japan Environmental Management Association for Industry, ecoleaf@jemai.or.jp

* In the case of an business entity certified as an Ecoleaf data-collection system, the names of certification auditors are written.

Product Environmental Information Data Sheet (PEIDS)



PCR name	EP and IJ printer	Product type	AccurioPress 6136P						
PCR-ID	AD-04	Product weight[kg]	345.0	Package[kg]	44.3	Weight total[kg]	389.3		

製品環境情報

//www.jemai.or.j

			Life Cycle Stage	l Init	Produ	uction	Distribution	llee	Dianagal	Beavala
In/Οι	ut ite	ms		Unit	Raw material	Product	Distribution	Use	Disposal	Recycle
				MJ	1.78E+04	7.48E+03	8.75E+02	8.39E+04	2.08E+02	-8.27E+03
		Energy (Consumption	Mcal	4.25E+03	1.79E+03	2.09E+02	2.00E+04	4.97E+01	-1.98E+03
		I I								
			Coal	kg	3.01E+02	4.71E+01	2.04E-03	3.94E+02	8.94E-01	-1.34E+02
		Eporav	Crude oil (as a fuel)	kg	1.09E+02	5.35E+01	1.91E+01	5.52E+02	2.55E+00	-4.46E+01
		Energy	Natural Gas	kg	2.80E+01	2.40E+01	2.95E-01	2.39E+02	4.73E-01	-1.13E+01
			Uranium ore	mg	2.30E-03	3.19E-03	1.38E-07	2.26E-02	6.05E-05	-3.34E-04
					2.002 00					
			Crude oil (as an	kg	3.11E+01	0	0	2.73E+02	0	0.405.04
			ingredients)							-3.18E+01
			Iron ore	kg	2.99E+02	0	0	2.02E+01	0	-1.28E+02
			Copper ore	kg	4.39E+00	0	0	0.00E+00	0	-1.57E+00
			Bauxite	kg	7.03E+00	0	0	1.82E+01	0	-1.01E+01
	ion	s e	Nickel ore	kg	3.12E+00	0	0	2.65E-01	0	-1.35E+00
	1 1 1 1 1 1 1 1	Exhaustible resources	Chromium ore		4.32E+00	0	0	3.66E-01	0	-1.87E+00
	onsu	esou		kg		-			-	
	e C(шe	Manganese ore	kg	1.99E+00	0	0	1.50E-01	0	-2.65E-01
	ourc n the	Material	Plumbous ore	kg	8.63E-02	0	0	0	0	-2.26E-02
	Resource Consumption from the environment		Tin ore	kg	0	0	0	0	0	0
			Zinc ore	kg	8.49E-01	0	0	0	0	-2.22E-01
			Gold ore	kg	0	0	0	0	0	0
					-					_
			Silver ore	kg	0	0	0	0	0	0
			Silica sand	kg	4.46E+00	0	0	2.35E-01	0	-8.96E-01
			Rock salt	kg	1.57E+01	3.03E-02	0	3.38E+00	1.48E-01	-7.09E+00
analyses			Limestone	kg	5.67E+01	0	0	5.10E+00	7.38E-01	-2.01E+01
linaly			Natural soda ash	kg	9.98E-02	0	0	0.00E+00	0	-1.36E-02
ny a			Wood			0	0		0	
nventory		Renewable resources		kg	6.54E+01	-	•	6.57E+01	÷	-5.24E+01
Inv		resources	Water	kg	5.86E+04	4.11E+04	1.54E+00	2.93E+05	7.18E+02	-2.69E+04
			CO2	kg	1.21E+03	3.68E+02	6.21E+01	3.66E+03	7.45E+01	-5.06E+02
			SOx	kg	8.57E-01	2.80E-01	3.74E-02	3.00E+00	4.17E-02	-5.58E-01
		to Atmosphere	NOx	kg	1.10E+00	2.26E-01	2.87E-01	3.87E+00	1.28E-01	-6.30E-01
			N2O	kg	6.69E-02	5.73E-03	1.05E-02	3.61E-01	2.25E-04	-3.65E-02
			CH4				3.70E-07	6.00E-02		
				kg	6.01E-03	8.52E-03			1.62E-04	-7.09E-04
			СО	kg	2.21E-01	5.44E-02	7.38E-02	6.41E-01	3.32E-02	-1.33E-01
			NMVOC	kg	1.18E-02	1.67E-02	7.25E-07	1.17E-01	3.17E-04	-1.39E-03
	nt Be		СхНу	kg	3.59E-02	1.20E-03	8.76E-03	1.03E-01	1.24E-03	-1.82E-02
	Emission/Discharge to the environment		dust	kg	1.59E-01	1.22E-02	2.77E-02	3.14E-01	8.02E-03	-8.68E-02
	/Dis		BOD	kg	_	_	_	_	_	_
	sion. e en		COD							
	mis: o the			kg	-	-	-	-	-	-
	ш÷	to Water system		kg	-	-	-	-	-	-
			P total	kg	-	-	-	-	-	-
			SS	kg	—	-	-	—	-	-
			Unspecified solid waste	kg	5.58E+00	1.97E-01	0	5.98E+01	1.83E+02	-4.82E+00
			Slag	kg	8.97E+01	0	0	6.30E+00	0	-3.74E+01
		to Soil system	Sludge		1.19E+01	0	0	3.91E+01	0	
		to our system		kg	1.190+01	0	0	3.912701	0	-2.04E+01
			Low emission	kg	1.61E-03	2.23E-03	9.67E-08	1.57E-02	4.22E-05	
			radioactive waste		1.012 00		0.072 00			-2.34E-04
	mption		Energy resources		0.545.00	1.005.00	1.055.04	1.005.00	4 105 .00	1 475 . 00
	duna		(crude oil equivalent)	kg	3.54E+02	1.39E+02	1.95E+01	1.28E+03	4.19E+00	-1.47E+02
	Cons	Exhaustible	Mineral resources							
	urce	resources	(Iron ore equivalent)	kg	3.53E+03	0	0	4.23E+02	0	-1.48E+03
ent	Reso									
assesment	by F									
ses	uo		Global warming	kg	1.22E+03	3.70E+02	6.50E+01	3.76E+03	7.46E+01	-5.16E+02
ass	sumption	to	(CO2 equivalent) Acidification							
ct à	m	Atmosphere		kg	1.63E+00	4.38E-01	2.38E-01	5.71E+00	1.31E-01	-9.99E-01
Impact	_									
<u>n</u>	ပိ									
	uo	to Water								
	nisi	system								
	by Emision Cor	to Soil								
	by	system								

[Notes for readers: EcoLeaf common rules]

I. Stage related

- A. "Production" stage is intended for two sub-stages listed below.
 - (1) "Raw material" production: consists of mining, transportation and raw material production.
 - (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal/recycle of consumables /maintenance goods (e.g. replacement parts).
- D. "Disposition/Recycle" stage is intended for environmental impacts by product disposition/recycle, and deduction by recycling (e.g. impact reduction of raw material production).
- E. "Recycle Effect" illustrates an indirect environmental influences to other products/services by use of reclaimed materials/parts, and/or by supply of used products to other businesses for material reclaim/parts reuse.
- Case 1: Use of reclaimed materials/parts: Sum of increase of environmental impact by collection activities of used materials/parts, and decrease by volume reduction of used materials/parts.
- Case 2: Supply of used products to other businesses for material reclaim/parts reuse: Sum of increase of environmental impact by materials/parts reclaiming process, and decrease by volume reduction of new materials/parts production.

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.
- B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO2 in case of "Global Warming"). A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.

B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

IV Data entry format

- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.
- C. Indicate "-" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
- (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

- A."Raw material" in "Production" includes environmental impacts generated during mining transportation material production phases of the main body of the printer and the toner cartridge enclosed in the printer. The environmental impacts are calculated using the eco-leaf basic unit DB for calculations.
- B. "Product" in "production" includes environmental impacts of processing of the parts (injection, blow-, press- and glass-molding). The environmental impacts from the parts assembly plant which is different from the main body assembly plant (such parts are clacified in "parts C") are calculated using the eco-leaf basic unit DB for calculations.
 - The impacts from the main body assembly plant are calculated using the quantitative data on environmental impacts in our assembly plant.
- C. Regarding the basis and the basic units for calculations during distribution stages The total distance of the transportation in Japan of 100km is used according to PCR (AD-04) and the transportation overseas includes the transportation by track in China and by ship between China and Japan.

D. Regarding the basis and the basic units for calculations during use and consumption stage

The power consumption is measured by the TEC test procedure according to PCR (AD-04). 11,097,600 sheets are printed in total during the use period of five years.

The toner consumption is summed up over the five years from the toner consumption data per sheet using our print pattern with 5% coverage. The production loads and the collection & recycling impacts of the toner cartridges used over the five years are included in this stage.

- E. The recycling impacts are calculated assuming that 40% of the end-of-life printers are recovered from users according to PCR (AD-04).
- The impacts are calculated with the remaining 60% following the disposal senario as general wastes.

F. The impacts of material production of recycled materials are included in the values with minus as a recycling effect.

Form3 (F-03-03)

Product data sheet

 (Input data and parameters for LCA)

 Document control no.
 F-03-03

 Product vendor
 KONICAMINOLTA,INC.

 EcoLeaf registration no.
 AD-18-946



PCR name	EP and IJ printer(PCR-ID:AD-04)	Product type	AccurioPress 6136P				
LCA/LCIA in units of:	1	Product weight[kg]	345.0	Package[kg]	44.3	Weight total[kg]	389.3

1. Product information (per unit): parts etc. by material and by process/assembly method

	Breakdown of primary	y materials		Math breakdown of part	s, which need to apply	Processing / Assembly I	Base Units (Parts B, C)
Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
Ordinary steel	2.81E+02	Rubber	2.82E+00	Press molding:Iron	2.82E+02		
Stainless steel	1.97E+01	Semiconductor circuit board	4.02E+00	Press molding:Nonfer rous metal	6.93E+00		
Aluminium	5.25E+00			Injection molding	3.23E+01		
Other metals	1.68E+00						
Glass	0.00E+00						
Thermoplastic resin	3.26E+01						
Wood	2.12E+01						
Paper	2.07E+01						
Subtotal	3.83E+02	Subtotal	6.85E+00				
	Total		3.89E+02	Subtotal	3.21E+02	Subtotal	

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO2, NO2 equivalent.

Ę	Classification	Energy	Energy	Material	Material		
sumption	Distribution	Electricity	Furnace urban	Industrial	Groundwater		
		(kWh)	gas (m ³)	water(kg)	(kg)		
Con	Quantity	4.80E+02	5.81E-01	5.22E+03	1.88E+01		
0	Note						
.ge	Classification	To Water system					
Emission/ Discharge	Distribution	Sewage(kg)					
En Dis	Quantity	5.23E+03					
	Note						

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

Distribution	Means of transportation	Freight by ship	Freight by ship	Freight by ship	Freight by ship	Diesel truck :20ton	Diesel truck :20ton	Diesel truck :20ton	Diesel truck :20ton
	Conditions	Load(kg · km)	Weight (kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)	Weight (kg)	Distance (km)	Loading Ratio(%w)
	Quantity	9.73E+05	3.89E+02	2.50E+03	1.00E+02	1.81E+05	3.89E+02	1.99E+02	4.28E+01
	Note								
ç	Means of transportation	Diesel truck	Diesel truck	Diesel truck	Diesel truck				
		:2ton	:2ton	:2ton	:2ton				
istribution	Conditions	Load(kg · km)	:2ton Weight (kg)	:2ton Distance (km)	:2ton Loading Ratio(%w)				
Distribution	Conditions Quantity				Loading				

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
Product	Distribution	Electricity (kWh)	Gasoline as fuel(kg)	Furnace urban gas (m ³)	Industrial water(kg)	Groundwater (kg)	Ordinary steel (kg)	Stainless steel (kg)	Aluminium (kg)
	Quantity	5.87E+03	1.36E+00	6.83E+01	3.86E+02	1.05E+04	1.90E+01	1.67E+00	1.72E+01
	Note								
	Classification	Consumption	Consumption	Consumption	Processing	Processing	Processing	Processing	Assembly
Product	Distribution	Thermoplastic resin(kg)	Paper(kg)	Rubber (kg)	Press:Iron(kg)	Press: Nonferrous(kg)	Injection molding(kg)	Blow molding (kg)	Parts assembly (kg)
Ē	Quantity	2.81E+02	3.08E+01	8.81E-02	1.68E+00	6.03E+00	1.18E+01	6.74E+01	6.74E+01
	Note								
	Classification	To Water system	Distribution						
Product	Distribution	Sewage(kg)	Diesel truck: 10ton (kg • km)						
	Quantity	1.06E+04	6.31E+04						
	Note								

4.2 Disposition/Recycle information on consumables and replacement parts

	Classification	Consumption	Consumption	Treatment	Treatment	Treatment	Treatment	Treatment	Treatment
nsumables	Distribution	Electricity (kWh)	Kerosene(kg)	Recycle: to iron(kg)	Recycle: to Aluminum(kg)	Recycle: to plastics(kg)	Recycle: to Paper(kg)	Industrial waste destruction by fire(kg)	Industrial waste inning(kg)
Consi	Quantity	2.91E+00	1.04E-01	8.27E+00	6.90E+00	2.10E+01	1.23E+01	7.26E+00	2.12E-01
	Note								
es	Classification	Treatment	Treatment	Deduction	Deduction	Deduction	Deduction		
Consumables	Distribution	Waste destruction by fire(kg)	Waste inning(kg)	lron(kg)	Aluminum(kg)	Plastics(kg)	Paper(kg)		
nsı	Quantity	5.03E+01	4.38E+01	-8.27E+00	-6.90E+00	-2.10E+01	-1.23E+01		
ŭ	Note								
	Classification	Distribution	Distribution						
sumables	Distribution	Diesel truck: 10ton (kg•km)	Diesel truck: 4ton (kg•km)						
Cons	Quantity	7.53E+03	9.11E+03						
	Note								

5. Disposition/Recycle stage information (per product): process method and scenarios

S	Classification	Consumption	Consumption	Treatment	Treatment	Treatment	Treatment	Treatment	Treatment
sumables	Distribution	Electricity (kWh)	Kerosene(kg)	Recycle: to iron(kg)	Recycle: to Aluminum(kg)	Recycle: to copper(kg)	Recycle: to plastics(kg)	Recycle: to Paper(kg)	Incineration: Industrial waste(kg)
Cons	Quantity	7.22E+00	2.57E-01	1.20E+02	2.10E+00	1.22E+00	1.28E+01	1.73E+01	2.31E+00
0	Note								
S	Classification	Treatment	Treatment	Treatment	Deduction	Deduction	Deduction	Deduction	Deduction
sumables	Distribution	Landfill: Industrial waste(kg)	Incineration to landfill (as ash)(kg)	Landfill: General waste(kg)	Iron(kg)	Aluminium (kg)	copper(kg)	Plastics(kg)	Paper(kg)
Cons	Quantity	4.12E-01	4.63E+01	1.76E+02	-1.20E+02	-2.10E+00	-1.22E+00	-1.28E+01	-1.73E+01
0	Note								
	Classification	Distribution	Distribution						
Consumables	Distribution	Diesel truck: 10ton (kg•km)	Diesel truck: 4ton (kg∙km)						
	Quantity	1.87E+04	2.26E+04						
	Note								

6. Others

A.Product information:

All the parts mass per unit sorted by materials and by processes/assembly are included. The motor mass is included in ordinary steel.

B.Production site information:

The energy consumption & material use during the main body assemby and cartridge & toner shipment are included. The environmental impacts that are exhausted from the production site in the atmosphere and the water system are included.

C.Distribution stage information:

The total distance of the transportation in Japan of 100km is used according to PCR (AD-04) and the transportation overseas includes the transportation by track in China and by ship between China and Japan.

D. Product and accessories subject to this analysis:

The power consumption is calculated assuming the use period of five years and 11,097,600 sheets printed during the use period according to the PCR (AD-04).

The toner consumption is summed up over the five years from the toner consumption data per sheet using our print pattern with 5% coverage.

The production impacts of the cartridges and toner used during the use period of five years are included.

The impacts of the maintenance parts used and the transportation impacts of the maintenace during the use period of five years are included in this stage.

E. Disposal/Recycle information on the consumables and the maintenance parts during use stage:

The recycling information of the toner, the developer, the drums and the maintainance parts used during the use period of five years are included .

The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus. Treatment of copper and deduction of copper include copper of " assembled circuit board".

Incineration of assembled circuit board is included "Incineration: Industrial waste".

F.Disposal/Recycle stage information:

The information on the products recovered from users is included.

The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus.

Treatment of copper and deduction of copper include copper of " assembled circuit board" .

Incineration of assembled circuit board is included "Incineration: Industrial waste".