

^{*} In the case of an business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

Form 2 (F-02B-03)

Product Environmental Information Data Sheet (PEIDS)

Document control no. F-02B-03						02B-03		Unit Function DB version 2.1						
Product vendor KONICA						Factor DB version	2.1		LEALS					
					18-9	,			設品環境情報 p://www.jemai.or.jp					
PCR name EP and IJ printer Product type							Due duret true e							
PCR name EP and IJ print			er	Product type Product weight[kg]	76.0	Deelegaelical	bizhub 308e 11.6		87.6					
	FU	- 7	שו		AD-04		5 1 51		Package[kg]	11.0	Weight total[kg]	87.0		
In/O	ut ite		_		Life Cycle Stage	Unit	Produ Raw material	Iction Product	Distribution	Use	Disposal	Recycle		
1170	utite	1115				MJ	4.83E+03	1.64E+03	3.69E+02	4.98E+03	6.00E+01	-1.65E+03		
	Energy Consumption					Mcal	1.15E+03	3.92E+02	8.81E+01	1.19E+03	1.43E+01	-3.93E+03		
				Coa	al	kg	4.98E+01	1.03E+01	8.62E-04	2.58E+01	2.95E-01	-1.91E+01		
				Cru	ide oil (as a fuel)	kg	4.03E+01	1.17E+01	8.06E+00	3.30E+01	6.88E-01	-1.18E+01		
			Energy	Nat	ural Gas	kg	7.83E+00	5.34E+00	1.24E-01	1.45E+01	1.54E-01	-1.87E+00		
				Ura	nium ore	mg	7.40E-04	6.97E-04	5.84E-08	1.37E-03	2.00E-05	-1.13E-04		
					Crude oil (as an ingredients)	kg	1.65E+01	0	0	1.40E+01	0	-8.36E+00		
					Iron ore	kg	4.55E+01	0	0	5.11E+00	0	-2.02E+01		
					Copper ore	kg	6.52E-01	0	0	1.09E-03	0	-1.99E-01		
					Bauxite	kg	6.82E-01	0	0	6.00E-01	0	-5.12E-01		
	nent	tible	ces		Nickel ore	kg	6.70E-02	0	0	8.24E-03	0	-3.01E-02		
	nsum ironn	Exhaustible	resources		Chromium ore	kg	1.06E-01	0	0	1.29E-02	0	-4.75E-02		
	e Co e env	EXI	_		Manganese ore	kg	2.46E-01	0	0	2.84E-02	0	-1.84E-02		
	Resource Consumption from the environment		Material		Plumbous ore	kg	3.60E-02	0	0	0	0	-9.58E-03		
	Reso				Tin ore	kg	0	0	0	0	0	0		
					Zinc ore	kg	3.55E-01	0	0	0	0	<u>-9.42E-02</u>		
					Gold ore	kg	0	0	0	0	0	0		
					Silver ore Silica sand	kg	0 2.55E+00	0	0	0 6.21E-02	0	0		
					Rock salt	kg ka	2.55E+00 7.79E+00	0 7.42E-03	0	5.30E-01	0 2.71E-02	-8.22E-01 -3.12E+00		
ses				-	Limestone	kg kg	9.80E+00	7.42E-03	0	1.08E+00	3.25E-01	-3.59E+00		
Inventory analyses				-	Natural soda ash	kg	2.17E-01	0	0	1.96E-04	0	-7.63E-02		
ory a		Bon	ewable		Wood	kg	1.68E+01	0	0	7.95E+00	0	-9.90E+00		
vent		resources			Water	kg	1.77E+04	9.14E+03	6.52E-01	1.71E+04	2.43E+02	-3.71E+03		
5		to Atmosphere			CO2	kg	2.80E+02	8.05E+01	2.62E+01	2.27E+02	3.36E+01	-9.08E+01		
					SOx	kg	1.64E-01	6.10E-02	1.47E-02	1.64E-01	1.81E-02	-5.35E-02		
					NOx	kg	3.32E-01	4.94E-02	1.02E-01	2.40E-01	4.52E-02	-1.17E-01		
					N2O	kg	2.11E-02	1.54E-03	4.71E-03	2.17E-02	6.26E-05	-7.38E-03		
					CH4	kg	1.97E-03	1.86E-03	1.56E-07	3.64E-03	5.34E-05	-2.92E-04		
					CO	kg	5.28E-02	1.19E-02	2.25E-02	3.75E-02	9.88E-03	-1.96E-02		
					NMVOC	kg	3.84E-03	3.65E-03	3.06E-07	7.13E-03	1.05E-04	-5.71E-04		
	arge				СхНу	kg	1.14E-02	2.98E-04	3.40E-03	6.04E-03	2.85E-04	-4.20E-03		
	Disch				dust	kg	4.04E-02	2.62E-03	1.03E-02	1.76E-02	2.68E-03	-1.54E-02		
	Emission/Discharge to the environment	to Water evetom		-	BOD COD	kg	-		-	-	-			
	Emiss the				N total	kg	-	-	-	-	-			
	<u> </u>	10 1	to Water system		P total	kg kg	_		_		-			
				-	SS	кg kg	_	_	_	_	_	_		
				Uns	specified solid waste	kg	1.61E+00	4.83E-02	0	5.43E+00	3.34E+01	-6.88E-01		
					Slag	kg	1.46E+01	0	0	1.55E+00	0.042.01	-6.05E+00		
		to S	oil system		Sludge	kg	1.26E+00	0	0	1.29E+00	0	-1.02E+00		
				r	Low emission radioactive waste	kg	5.18E-04	4.86E-04	4.08E-08	9.52E-04	1.39E-05	-7.88E-05		
	sumption			(cr	Energy resources rude oil equivalent)	kg	8.78E+01	3.04E+01	8.21E+00	7.83E+01	1.23E+00	-2.72E+01		
tent	by Resource Consumption		haustible sources		Mineral resources ron ore equivalent)	kg	2.72E+02	0	0	2.17E+01	0	-9.57E+01		
esm					Global warming	k-	2 265+02	9 10E+01	2 755+01	2 22E±02	2 27E+01	-0.205+01		
ISSE	ptio		to		(CO2 equivalent) Acidification	kg	2.86E+02	8.10E+01	2.75E+01	2.33E+02	3.37E+01	-9.28E+01		
Impact assesment	unsuo	Atı	nosphere	-	Acidification (SO2 equivalent)	kg	3.97E-01	9.56E-02	8.63E-02	3.32E-01	4.98E-02	-1.36E-01		
-	Emision Consumption		o Water system											
	by Em		to Soil system											

[Notes for readers: EcoLeaf common rules]

- . I. Stage related
- A. "Production" stage is intended for two sub-stages listed below.
- (1) "Raw material" production: consists of mining, transportation and raw material production.
- (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal/recycle of consumables
- /maintenance goods (e.g. replacement parts). D. "Disposition/Recycle" stage is intended for environmental impacts by product disposition/recycle, and deduction by recycling
- (e.g. impact reduction of raw material production).
 E. "Recycle Effect" illustrates an indirect environmental influences to other products/services by use of reclaimed materials/parts, and/or by supply of
- used products to other businesses for material reclaim/parts reuse. Case 1: Use of reclaimed materials/parts: Sum of increase of environmental impact by collection activities of used materials/parts, and decrease
- by volume reduction of used materials/parts.
- Case 2: Supply of used products to other businesses for material reclaim/parts reuse: Sum of increase of environmental impact by materials/parts reclaiming process, and decrease by volume reduction of new materials/parts production.

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore. B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate,
- which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III Impact analyses

- Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO2 in case of "Global Warming"). A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.
- B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.
- IV Data entry format
- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results. C. Indicate "-" if calculation nor estimation can not be done, in order to differentiate to indicate "zero"
- (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

- [Notes for readers: Target product specific] A."Raw material" in "Production" includes environmental impacts generated during mining transportation material production phases of the main body of the printer and the toner cartridge enclosed in the printer. The environmental impacts are calculated using the eco-leaf basic unit DB for calculations.
- B. " Product" in "production" includes environmental impacts of processing of the parts (injection, blow-, press- and glass-molding). The environmental impacts from the parts assembly plant which is different from the main body assembly plant (such parts are clacified in "parts C") are calculated using the eco-leaf basic unit DB for calculations. The impacts from the main body assembly plant are calculated using the quantitative data on environmental impacts in our assembly plant.
- C. Regarding the basis and the basic units for calculations during distribution stages The total distance of the transportation in Japan of 100km is used according to PCR (AD-04) and the transportation overseas includes the transportation by track in China and by ship between China and Japan.
- D. Regarding the basis and the basic units for calculations during use and consumption stage The power consumption is measured by the TEC test procedure according to PCR (AD-04). 540,000 sheets are printed in total during the use period of five years.

The toner consumption is summed up over the five years from the toner consumption data per sheet using our print pattern with 5% coverage. The production loads and the collection & recycling impacts of the toner cartridges used over the five years are included in this stage.

- E. The recycling impacts are calculated assuming that 40% of the end-of-life printers are recovered from users according to PCR (AD-04). The impacts are calculated with the remaining 60% following the disposal senario as general wastes.
- F. The impacts of material production of recycled materials are included in the values with minus as a recycling effect.

Form3 (F-03-03)

Product data sheet (Input data and parameters for LCA) F-03-03



 Document control no.
 F-03-03

 Product vendor
 KONICAMINOLTA,INC.

 EcoLeaf registration no.
 AD-18-961

 PCR name
 EP and IJ printer(PCR-ID:AD=04)
 Product type
 bizhub 308e

 LCA/LCIA in units of:
 1
 Product weight[kg]
 76.0
 Package[kg]
 11.6
 Weight total[kg]
 87.6

 1. Product information (per unit): parts etc. by material and by process/assembly method
 1
 Product information (per unit): parts etc. by material and by process/assembly method
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1
 1

	Breakdown of primar	y materials		Math breakdown of parts, which need to apply Processing / Assembly Base Units (Parts B, C			
Material name	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)	
Ordinary steel	4.37E+01	Rubber	1.79E-01	Press molding:lron	4.27E+01		
Stainless steel	Stainless steel 4.18E-01 Semiconductor circuit b		1.64E+00	Press molding:Nonfe rrous metal	1.28E+00		
Aluminium	5.58E-01			Injection molding	2.70E+01		
Other metals	7.21E-01						
Glass	2.11E+00						
Thermoplastic resin	2.75E+01						
Wood	5.40E+00						
Paper	5.35E+00						
Subtotal	8.58E+01	Subtotal	1.82E+00				
	8 76E+01	Subtotal	7 10E+01	Subtotal			

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

c	Classification	Energy	Energy	Material	Material				
Consumption	Distribution	Electricity	Furnace urban	Industrial	Groundwater				
E E		(kWh)	gas (m ³)	water(kg)	(kg)				
ous	Quantity	1.06E+02	2.45E-01	1.28E+03	1.57E+01				
0	Note								
	Classification	To Water							
Emission/ Discharge	Classification	system							
che	Distribution	Sewage(kg)							
Dis	Quantity	1.28E+03							
	Note								
3. Distribu	ution stage information (per unit): means, distan	ce, loading ratio	, consumptions	and emissions/	discharges.			
	Means of transportation	Freight by ship	Freight by ship	Freight by ship	Freight by ship	Diesel truck :20ton	Diesel truck :20ton	Diesel truck :20ton	Diesel truck :20ton
	Conditions	Load(kg•km)	Malak (las)		Loading				
		Load(kg kiii)	Weight (kg)	Distance (km)	Ratio(%w)	Load(kg•km)	Weight (kg)	Distance (km)	Loading Ratio(%w)
E	Quantity	4.38E+05	8.76E+01	5.00E+03		Load(kg•km) 5.08E+04	Weight (kg) 8.76E+01	Distance (km) 2.59E+02	
oution	Quantity Note				Ratio(%w)			1. A. A.	Ratio(%w)
Distribution	,	4.38E+05 Diesel truck	8.76E+01 Diesel truck	5.00E+03 Diesel truck	Ratio(%w) 1.0E+02 Diesel truck			1. A. A.	Ratio(%w)
Distribution	Note	4.38E+05	8.76E+01	5.00E+03	Ratio(%w) 1.0E+02 Diesel truck :2ton			1. A. A.	Ratio(%w)
Distribution	Note	4.38E+05 Diesel truck	8.76E+01 Diesel truck	5.00E+03 Diesel truck	Ratio(%w) 1.0E+02 Diesel truck			1. A. A.	Ratio(%w)
Distribution	Note Means of transportation	4.38E+05 Diesel truck :2ton	8.76E+01 Diesel truck :2ton	5.00E+03 Diesel truck :2ton	Ratio(%w) 1.0E+02 Diesel truck :2ton Loading			1. A. A.	Ratio(%w)

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

.1 Product and accessories subject to this analysis sification Consumption Consumption Consumption Consumption Consumption Consumption Consumption Electricity Gasoline as Furnace urban Industrial Groundwater Ordinary steel Stainless steel Aluminium Product Distribution (kWh) 3.42E+02 fuel(kg) 1.81E-01 water(kg) 8.68E+01 (kg) 4.92E+00 gas (m³) 4.56E+00 (kg) 5.66E+02 (kg) 5.15E-02 (kg) 5.67E-01 Quantity Classification Processing Processing Consumption Consumption Consumption Consumption Processing Processing Thermoplastic resin(kg) Press:Iron Injection Blow molding molding(kg) (kg) 9.17E-01 5.64E+00 Product Press: Nonferrous(kg) Blow molding Distribution Glass(kg) Paper(kg) Rubber(kg) (kg) 5.06E+00 Quantity Note 1.41E+01 0.00E+00 3.73E+00 1.19E-01 2.78E-01 To Water Classification Assembly system Product Parts embly(kg) Distribution Sewage (kg) 5.01E+02 Quantity 5.64E+00 Note Classification Distribution Distribution Distribution Diesel truck: 20ton (kg•km) Diesel truck: 10ton (kg•km) Distribution Freight by ship (kg·km) Product Quantity 1.43E+04 2.10E+03 3.05E+03 Note 4.2 Disposition/Recycle information on consumables and replacement parts Consumption Consumption Treatment Treatment Treatment Treatment Treatment Treatment Electricity (kWh) Recycle: to iron(kg) Recycle: to Aluminum(kg) Recycle: to plastics(kg) Recycle: to Paper(kg) Industrial waste destruction by fire(kg) Industrial was inning(kg) Distribution Kerosene(kg) Cons Quantity 2.94E-01 1.04E-02 1.99E+00 2.27E-01 2.03E+00 1.49E+00 1.02E-01 2.07E-02 Note Treatment Treatment Deduction Deduction Deduction Deduction Waste destruction by fire(kg) Waste Distribution Plastics(kg) Iron(kg) Aluminum(kg) Paper(kg) innina(ka) Consi Quantity 5.39E+00 4.11E+00 -1.99E+00 -2.27E-01 -2.03E+00 -1.49E+00 Note Distribution Classification Distribution les Diesel truck Diesel truck 4ton Distribution (ka•km) (kg·km) Cons Quantity Note 7.60E+02 8.44E+02

5. Disposition/Recycle stage information (per product): process method and scenarios

8	2	Classification	Consumption	Consumption	Treatment	Treatment	Treatment	Treatment	Treatment	Treatment
andomi		Distribution	Electricity (kWh)	Kerosene(kg)	Recycle: to iron(kg)	Recycle: to Aluminum(kg)	Recycle: to copper(kg)	Recycle: to Glass(kg)	Recycle: to plastics(kg)	Recycle: to Paper(kg)
iouoj	5	Quantity	1.64E+00	5.82E-02	1.79E+01	2.23E-01	5.12E-01	8.43E-01	1.09E+01	4.53E+00
0	· [Note								
		Classification	Treatment	Treatment	Treatment	Treatment	Deduction	Deduction	Deduction	Deduction
antan		Distribution	Incineration: Industrial waste(kg)	Landfill: Industrial waste(kg)	Incineration to landfill (as ash)(kg)	Landfill: General waste(kg)	Iron(kg)	Aluminium (kg)	copper(kg)	Glass(kg)
ê	3	Quantity	4.99E-01	1.55E-01	2.31E+01	2.97E+01	-1.79E+01	-2.23E-01	-5.12E-01	-8.43E-01
		Note								
		Classification	Deduction	Deduction	Distribution	Distribution				
oneumahlae		Distribution	Plastics(kg)	Paper(kg)	Diesel truck: 10ton (kg•km)	Diesel truck: 4ton (kg•km)				
č	3	Quantity	-1.09E+01	-4.53E+00	4.24E+03	5.13E+03				
		Note								

6. Others

A.Product information:

All the parts mass per unit sorted by materials and by processes/assembly are included. The motor mass is included in ordinary steel.

B.Production site information:

The energy consumption & material use during the main body assemby and cartridge & toner shipment are included. The environmental impacts that are exhausted from the production site in the atmosphere and the water system are included.

C.Distribution stage information: The total distance of the transportation in Japan of 100km is used according to PCR (AD-04) and the transportation overseas includes the transportation by track in China and by ship between China and Japan.

D. Product and accessories subject to this analysis: The power consumption is calculated assuming the use period of five years and 540,000 sheets printed during the use period according to the PCR (AD-04). The toner consumption is summed up over the five years from the toner consumption data per sheet using our print pattern with 5%

coverage. The production impacts of the cartridges and toner used during the use period of five years are included. The impacts of the maintenance parts used and the transportation impacts of the maintenace during the use period of five years are included in this stage.

E. Disposal/Recycle information on the consumables and the maintenance parts during use stage: The recycling information of the toner, the developer, the drums and the maintainance parts used during the use period of five years

The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus.

Treatment of copper and deduction of copper include copper of " assembled circuit board" . Incineration of assembled circuit board is included "Incineration: Industrial waste".

F.Disposal/Recycle stage information: The information on the products recovered from users is included.

The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus. Treatment of copper and deduction of copper include copper of " assembled circuit board". Incineration of assembled circuit board is included "Incineration: Industrial waste".