

\* In the case of an business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

## Form 2 (F-02B-03)

# Product Environmental Information Data Sheet (PEIDS)

Document control no. F-02B-03								Unit Function DB version 2.1							
Product vendor KONICA						Factor DB version	2.1		LIMATO						
Eco			gistration	no.		-18-9	,	Characterization Factor DB Version 製品環境情報							
	DOI	D													
			ame -ID		EP and IJ print AD-04	er	Product type Product weight[kg]	76.0	Package[kg]	bizhub 368e 11.6	Weight total[kg]	87.6			
	FU		U		AD-04				Fackage[kg]	11.0	weight total[kg]	87.0			
	Life Cycle Stage Unit Raw material						ection Product	Distribution	Use	Disposal	Recycle				
in/O	ut ite						4.83E+03	1.64E+03	3.69E+02	7.23E+03	6.00E+01	-1.87E+03			
	Energy C		gy Consumption		Mcal	1.15E+03	3.92E+02	8.81E+01	1.73E+03	1.43E+01	-4.47E+03				
		1		Coal		kg	4.98E+01	1.03E+01	8.62E-04	4.14E+01	2.95E-01	-2.21E+01			
				Cru	de oil (as a fuel)	kg	4.03E+01	1.17E+01	8.06E+00	4.77E+01	6.88E-01	-1.31E+01			
			Energy	Nat	ural Gas	kg	7.83E+00	5.34E+00	1.24E-01	2.04E+01	1.54E-01	-2.11E+00			
				Ura	nium ore	mg	7.40E-04	6.97E-04	5.84E-08	1.90E-03	2.00E-05	-1.17E-04			
					Crude oil (as an ingredients)	kg	1.65E+01	0	0	2.11E+01	0	-9.59E+00			
					Iron ore	kg	4.55E+01	0	0	1.33E+01	0	-2.35E+01			
					Copper ore	kg	6.52E-01	0	0	1.82E-03	0	-1.99E-01			
	_				Bauxite	kg	6.82E-01	0	0	9.78E-01	0	-6.63E-01			
	nent	ible	Sec		Nickel ore	kg	6.70E-02	0	0	3.48E-02	0	-4.07E-02			
	ironm	Exhaustible	resources		Chromium ore	kg	1.06E-01	0	0	5.17E-02	0	-6.31E-02			
	e Col	Ш×	_		Manganese ore	kg	2.46E-01	0	0	7.61E-02	0	-2.26E-02			
	Resource Consumption from the environment		Material		Plumbous ore	kg	3.60E-02	0	0	0	0	-9.59E-03			
	Res				Tin ore	kg	0	0	0	0	0	0			
					Zinc ore	kg	3.55E-01	0	0	0	0	<u>-9.43E-02</u>			
				-	Gold ore	kg	0	0	0	0	0	0			
					Silver ore Silica sand	kg	0 2.55E+00	0	0	0 2.11E-01	0	0			
					Rock salt	kg ka	2.55E+00 7.79E+00	0 7.42E-03	0	9.56E-01	0 2.71E-02	-8.63E-01			
ses					Limestone	kg kg	9.80E+00	7.42E-03	0	2.75E+00	3.25E-01	-3.28E+00 -4.14E+00			
nalys				-	Natural soda ash	kg	2.17E-01	0	0	6.20E-03	0	-7.87E-02			
Inventory analyses		Pa	newable		Wood	кg kg	1.68E+01	0	0	1.09E+01	0	-1.11E+01			
vent			resources		Water	kg	1.77E+04	9.14E+03	6.52E-01	2.46E+04	2.43E+02	-4.26E+03			
5					CO2	kg	2.80E+02	8.05E+01	2.62E+01	3.37E+02	3.37E+01	-1.03E+02			
					SOx	kg	1.64E-01	6.10E-02	1.47E-02	2.42E-01	1.81E-02	-6.28E-02			
			to Atmosphere		NOx	kg	3.32E-01	4.94E-02	1.02E-01	3.56E-01	4.53E-02	-1.32E-01			
					N2O	kg	2.11E-02	1.54E-03	4.71E-03	3.14E-02	6.26E-05	-8.36E-03			
		to A			CH4	kg	1.97E-03	1.86E-03	1.56E-07	5.05E-03	5.34E-05	-3.00E-04			
					СО	kg	5.28E-02	1.19E-02	2.25E-02	5.69E-02	9.88E-03	-2.21E-02			
					NMVOC	kg	3.84E-03	3.65E-03	3.06E-07	9.89E-03	1.05E-04	-5.88E-04			
	arge				CxHy	kg	1.14E-02	2.98E-04	3.40E-03	9.26E-03	2.85E-04	-4.72E-03			
	Disch ironm				dust	kg	4.04E-02	2.62E-03	1.03E-02	2.82E-02	2.68E-03	-1.75E-02			
	ission/Discharge the environment				BOD	kg	-	-	-	-	-	-			
	Emissi to the	to	Vater system		COD N total	kg	-	-	-	-	-	-			
		10 1	valer system	-	P total	kg ka			-	_	_	_			
					SS	kg kg	_	_	_	_	_	_			
				Uns	pecified solid waste	кg kg	1.61E+00	4.83E-02	0	- 1.17E+01		-7.83E-01			
				0113	Slag	kg	1.46E+01	4.03E-02	0	4.04E+00	0	-7.05E+00			
		to S	Soil system		Sludge	kg	1.26E+00	0	0	2.10E+00	0	-1.34E+00			
				r	Low emission adioactive waste	kg	5.18E-04	4.86E-04	4.08E-08	1.32E-03	1.39E-05	-8.17E-05			
	sumption			(cr	Energy resources rude oil equivalent)	kg	8.78E+01	3.04E+01	8.21E+00	1.14E+02	1.23E+00	-3.08E+01			
nent	by Resource Consumption		haustible sources	N	lineral resources on ore equivalent)	kg	2.72E+02	0	0	5.70E+01	0	-1.09E+02			
ssesn			4.		Global warming (CO2 equivalent)	kg	2.86E+02	8.10E+01	2.75E+01	3.45E+02	3.37E+01	-1.05E+02			
Impact assesment	dunsuc	At	to mosphere		Acidification (SO2 equivalent)	kg	3.97E-01	9.56E-02	8.63E-02	4.91E-01	4.98E-02	-1.55E-01			
Ш	Emision Consumption		o Water system												
	by Emi		to Soil system												

[Notes for readers: EcoLeaf common rules]

- . I. Stage related
- A. "Production" stage is intended for two sub-stages listed below.
- (1) "Raw material" production: consists of mining, transportation and raw material production.
- (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal/recycle of consumables
- /maintenance goods (e.g. replacement parts). D. "Disposition/Recycle" stage is intended for environmental impacts by product disposition/recycle, and deduction by recycling
- (e.g. impact reduction of raw material production).
   E. "Recycle Effect" illustrates an indirect environmental influences to other product/services by use of reclaimed materials/parts, and/or by supply of
- used products to other businesses for material reclaim/parts reuse. Case 1: Use of reclaimed materials/parts: Sum of increase of environmental impact by collection activities of used materials/parts, and decrease
- by volume reduction of used materials/parts.
- Case 2: Supply of used products to other businesses for material reclaim/parts reuse: Sum of increase of environmental impact by materials/parts reclaiming process, and decrease by volume reduction of new materials/parts production.

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore. B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate,
- which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

#### III Impact analyses

- Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO2 in case of "Global Warming"). A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.
- B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.
- IV Data entry format
- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results. C. Indicate "-" if calculation nor estimation can not be done, in order to differentiate to indicate "zero"
- (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

- [Notes for readers: Target product specific] A."Raw material" in "Production" includes environmental impacts generated during mining transportation material production phases of the main body of the printer and the toner cartridge enclosed in the printer. The environmental impacts are calculated using the eco-leaf basic unit DB for calculations.
- B. " Product" in "production" includes environmental impacts of processing of the parts (injection, blow-, press- and glass-molding). The environmental impacts from the parts assembly plant which is different from the main body assembly plant (such parts are clacified in "parts C") are calculated using the eco-leaf basic unit DB for calculations. The impacts from the main body assembly plant are calculated using the quantitative data on environmental impacts in our assembly plant.
- C. Regarding the basis and the basic units for calculations during distribution stages The total distance of the transportation in Japan of 100km is used according to PCR (AD-04) and the transportation overseas includes the transportation by track in China and by ship between China and Japan.
- D. Regarding the basis and the basic units for calculations during use and consumption stage The power consumption is measured by the TEC test procedure according to PCR (AD-04). 777,600 sheets are printed in total during the use period of five years.

The toner consumption is summed up over the five years from the toner consumption data per sheet using our print pattern with 5% coverage. The production loads and the collection & recycling impacts of the toner cartridges used over the five years are included in this stage.

- E. The recycling impacts are calculated assuming that 40% of the end-of-life printers are recovered from users according to PCR (AD-04). The impacts are calculated with the remaining 60% following the disposal senario as general wastes.
- F. The impacts of material production of recycled materials are included in the values with minus as a recycling effect.

Form3 (F-03-03)

Product data sheet ers for LCA)



(Input data and paramete F-03-03 KONICAMINOLTA,INC. AD-18-960 Document control no. Product vendor EcoLeaf registration no.

EP and IJ printer (PCR-ID:AD-04) bizhub 368e 11.6 Weight total[kg] PCR name LCA/LCIA in units of: Product type
76.0 Package[kg] Product weight[kg] 87.6 1. Product information (per unit): parts etc. by material and by process/assembly method

	Breakdown of primar	y materials		Math breakdown of par	Base Units (Parts B, C)		
Material name	Material name Weight (kg) Material name				Weight (kg)	Process name	Weight (kg)
Ordinary steel	Ordinary steel 4.37E+01		1.79E-01	Press molding:lron	4.27E+01		
Stainless steel	4.18E-01	Semiconductor circuit board	1.64E+00	Press molding:Nonfe rrous metal	1.28E+00		
Aluminium	5.58E-01			Injection molding	2.70E+01		
Other metals	7.21E-01						
Glass	2.11E+00						
Thermoplastic resin	2.75E+01						
Wood	5.40E+00						
Paper	Paper 5.35E+00						
Subtotal							
	Total		9 785-01	Subtotal	7 105+01	Subtotal	

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

	01 17 11	_	_						
5	Classification	Energy	Energy	Material	Material				
pti	Distribution	Electricity	Furnace urban	Industrial	Groundwater				
Ling Ling		(kWh)	gas (m <sup>3</sup> )	water(kg)	(kg)				
Consumption	Quantity	1.06E+02	2.45E-01	1.28E+03	1.57E+01				
0	Note								
	01	To Water							
ge n/	Classification	system							
Emission/ Discharge	Distribution	Sewage(kg)							
ois c	Quantity	1.28E+03							
	Note	1.202.00							
	1000								
	Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.								
3. Distrib	ution stage information (per unit	:): means, distan	ice, loading ratio	o, consumptions	and emissions/	discharges.			
3. Distrib		(	Freight by	Freight by	Freight by	Diesel truck	Diesel truck	Diesel truck	Diesel truck
3. Distribi	Means of transportation	Freight by ship					Diesel truck :20ton	Diesel truck :20ton	Diesel truck :20ton
3. Distribi	Means of transportation	Freight by ship	Freight by ship	Freight by ship	Freight by ship	Diesel truck :20ton	:20ton	:20ton	:20ton
3. Distribi		(	Freight by	Freight by	Freight by ship Loading	Diesel truck			:20ton Loading
	Means of transportation Conditions	Freight by ship Load(kg•km)	Freight by ship Weight (kg)	Freight by ship Distance (km)	Freight by ship Loading Ratio(%w)	Diesel truck :20ton Load(kg•km)	:20ton Weight (kg)	:20ton Distance (km)	:20ton Loading Ratio(%w)
	Means of transportation Conditions Quantity	Freight by ship	Freight by ship	Freight by ship	Freight by ship Loading	Diesel truck :20ton	:20ton	:20ton	:20ton Loading
	Means of transportation Conditions	Freight by ship Load(kg•km) 4.38E+05	Freight by ship Weight (kg) 8.76E+01	Freight by ship Distance (km) 5.00E+03	Freight by ship Loading Ratio(%w) 1.0E+02	Diesel truck :20ton Load(kg•km)	:20ton Weight (kg)	:20ton Distance (km)	:20ton Loading Ratio(%w)
3. Distribi	Means of transportation Conditions Quantity	Freight by ship Load(kg•km) 4.38E+05 Diesel truck	Freight by ship Weight (kg) 8.76E+01 Diesel truck	Freight by ship Distance (km) 5.00E+03 Diesel truck	Freight by ship Loading Ratio(%w) 1.0E+02 Diesel truck	Diesel truck :20ton Load(kg•km)	:20ton Weight (kg)	:20ton Distance (km)	:20ton Loading Ratio(%w)
	Means of transportation Conditions Quantity Note	Freight by ship Load(kg•km) 4.38E+05	Freight by ship Weight (kg) 8.76E+01	Freight by ship Distance (km) 5.00E+03	Freight by ship Loading Ratio(%w) 1.0E+02 Diesel truck :2ton	Diesel truck :20ton Load(kg•km)	:20ton Weight (kg)	:20ton Distance (km)	:20ton Loading Ratio(%w)
	Means of transportation Conditions Quantity Note	Freight by ship Load(kg•km) 4.38E+05 Diesel truck :2ton	Freight by ship Weight (kg) 8.76E+01 Diesel truck :2ton	Freight by ship Distance (km) 5.00E+03 Diesel truck :2ton	Freight by ship Loading Ratio(%w) 1.0E+02 Diesel truck :2ton Loading	Diesel truck :20ton Load(kg•km)	:20ton Weight (kg)	:20ton Distance (km)	:20ton Loading Ratio(%w)
	Means of transportation Conditions Quantity Note Means of transportation Conditions	Freight by ship Load(kg•km) 4.38E+05 Diesel truck :2ton Load(kg•km)	Freight by ship Weight (kg) 8.76E+01 Diesel truck	Freight by ship Distance (km) 5.00E+03 Diesel truck	Freight by ship Loading Ratio(%w) 1.0E+02 Diesel truck :2ton	Diesel truck :20ton Load(kg•km)	:20ton Weight (kg)	:20ton Distance (km)	:20ton Loading Ratio(%w)
	Means of transportation Conditions Quantity Note Means of transportation	Freight by ship Load(kg•km) 4.38E+05 Diesel truck :2ton	Freight by ship Weight (kg) 8.76E+01 Diesel truck :2ton	Freight by ship Distance (km) 5.00E+03 Diesel truck :2ton	Freight by ship Loading Ratio(%w) 1.0E+02 Diesel truck :2ton Loading	Diesel truck :20ton Load(kg•km)	:20ton Weight (kg)	:20ton Distance (km)	:20ton Loading Ratio(%w)

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.
 4.1 Product and accessories subject to this analysis

4.1 FIUU	accessories subject to th	iis allalysis							
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
5	Distribution	Electricity	Gasoline as	Furnace urban	Industrial	Groundwater	Ordinary steel	Stainless steel	Aluminium
Product	Distribution	(kWh)	fuel(kg)	gas (m <sup>3</sup> )	water(kg)	(kg)	(kg)	(kg)	(kg)
đ	Quantity	4.59E+02	1.81E-01	6.21E+00	2.47E+02	7.87E+02	1.28E+01	2.19E-01	9.25E-01
	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Processing	Processing	Processing	Processing
Product	Distribution	Glass(kg)	Thermoplastic resin(kg)	Paper(kg)	Rubber(kg)	Press:Iron (kg)	Press: Nonferrous(kg)	Injection molding (kg)	Blow molding (kg)
2	Quantity	7.00E-02	2.15E+01	5.14E+00	2.08E-01	1.45E+01	2.78E-01	1.40E+00	8.02E+00
	Note								
-	Classification	Assembly	To Water system						
Product	Distribution	Parts assembly(kg)	Sewage(kg)						
	Quantity	8.02E+00	8.31E+02						
	Note							Stainless steel (kg) 2.19E-01 Processing Injection molding(kg)	
	Classification	Distribution	Distribution	Distribution					
Product	Distribution	Freight by ship (kg·km)	Diesel truck: 20ton (kg•km)	Diesel truck: 10ton (kg•km)					
-	Quantity	2.20E+04	3.90E+03	4.38E+03					
	Note								
4.2 Dispo	sition/Recycle information on c	onsumables and	replacement pa	arts		•	•	•	
	Classification	Consumption	Consumption	Treatment	Treatment	Treatment	Treatment	Treatment	Treatment
Consumables	Distribution	Electricity (kWh)	Kerosene(kg)	Recycle: to iron(kg)	Recycle: to Aluminum(kg)	Recycle: to plastics(kg)	Recycle: to Paper(kg)	destruction by	Industrial waste inning(kg)
Ŝ	Quantity	5.56E-01	1.98E-02	5.19E+00	3.70E-01	3.42E+00	2.06E+00	1.68E-01	3.48E-02
	Note								
	Classification	Treatment	Treatment	Deduction	Deduction	Deduction	Deduction		
Consumables	Distribution	Waste destruction by fire(kg)	Waste inning(kg)	lron(kg)	Aluminum(kg)	Plastics(kg)	Paper(kg)		
Co	Quantity	8.39E+00	9.61E+00	-5.19E+00	-3.70E-01	-3.42E+00	-2.06E+00		
	Note								
	Classification	Distribution	Distribution						
Consumables	Distribution	Diesel truck: 10ton (kg•km)	Diesel truck: 4ton (kg•km)						
ů	Quantity	1.44E+03	1.62E+03						
	Note								

### 5. Disposition/Recycle stage information (per product): process method and scenarios

5	a	Classification	Consumption	Consumption	Treatment	Treatment	Treatment	Treatment	Treatment	Treatment
8	umanes	Distribution	Electricity (kWh)	Kerosene(kg)	Recycle: to iron(kg)	Recycle: to Aluminum(kg)	Recycle: to copper(kg)	Recycle: to Glass(kg)	Recycle: to plastics(kg)	Recycle: to Paper(kg)
	002	Quantity	1.64E+00	5.83E-02	1.79E+01	2.23E-01	5.12E-01	8.43E-01	1.09E+01	4.53E+00
c	د	Note								
		Classification	Treatment	Treatment	Treatment	Treatment	Deduction	Deduction	Deduction	Deduction
	ISUITADIES	Distribution	Incineration: Industrial waste(kg)	Landfill: Industrial waste(kg)	Incineration to landfill (as ash)(kg)	Landfill: General waste(kg)	Iron(kg)	Aluminium (kg)	copper(kg)	Glass(kg)
e c	3	Quantity	5.01E-01	1.55E-01	2.31E+01	2.97E+01	-1.79E+01	-2.23E-01	-5.12E-01	-8.43E-01
		Note								
		Classification	Deduction	Deduction	Distribution	Distribution				
	OIISUIIIADIES	Distribution	Plastics(kg)	Paper(kg)	Diesel truck: 10ton (kg•km)	Diesel truck: 4ton (kg•km)				
ĉ	3	Quantity	-1.09E+01	-4.53E+00	4.24E+03	5.13E+03				
		Note								

6. Others

A.Product information:

All the parts mass per unit sorted by materials and by processes/assembly are included. The motor mass is included in ordinary steel.

B.Production site information:

The energy consumption & material use during the main body assemby and cartridge & toner shipment are included. The environmental impacts that are exhausted from the production site in the atmosphere and the water system are included.

C.Distribution stage information: The total distance of the transportation in Japan of 100km is used according to PCR (AD-04) and the transportation overseas includes the transportation by track in China and by ship between China and Japan.

D. Product and accessories subject to this analysis: The power consumption is calculated assuming the use period of five years and 777,600 sheets printed during the use period according to the PCR (AD-04). The toner consumption is summed up over the five years from the toner consumption data per sheet using our print pattern with 5%

coverage. The production impacts of the cartridges and toner used during the use period of five years are included. The impacts of the maintenance parts used and the transportation impacts of the maintenace during the use period of five years are included in this stage.

E. Disposal/Recycle information on the consumables and the maintenance parts during use stage: The recycling information of the toner, the developer, the drums and the maintainance parts used during the use period of five years

The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus.

Treatment of copper and deduction of copper include copper of " assembled circuit board" . Incineration of assembled circuit board is included "Incineration: Industrial waste".

F.Disposal/Recycle stage information: The information on the products recovered from users is included.

The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus. Treatment of copper and deduction of copper include copper of " assembled circuit board". Incineration of assembled circuit board is included "Incineration: Industrial waste".