

Third party verifier: The third party verifier \* : Kazuo Naito

Programme operator: Japan Environmental Management Association for Industry, ecoleaf@jemai.or.jp

\* In the case of an business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

# Form 2 (F-02B-03)

# Product Environmental Information Data Sheet (PEIDS)

Document control no. F-02B-03								Unit Fu	nction DB version	2.1		ECO		
Product vendor KONICAMINOLTA ,INC.									Factor DB version	2.1	-	LI MATO		
EcoLeaf registration no. AD-17-853					53					<mark>提品環境情報</mark> p://www.jemai.or.jp				
	PC	R na	me		EP and IJ print	er	Product type	bizhub_C3851						
							Product weight[kg]	49.2	Package[kg]	8.9	Weight total[kg]	58.1		
	Life Cycle Stage Produc						Brodu	uction	0101		0 101			
In/O	In/Out items Unit Raw material							Product	Distribution	Use	Disposal	Recycle		
	Energy Consumption					MJ	3.89E+03	5.68E+02	2.14E+02	2.04E+04	4.17E+01	-3.86E+03		
		Energy Consumption				Mcal	9.29E+02	1.36E+02	5.12E+01	4.86E+03	9.96E+00	-9.22E+02		
				Coa	-	kg	3.15E+01	3.45E+00	5.01E-04	1.21E+02	2.15E-01	-3.60E+01		
			Energy		de oil (as a fuel) ural Gas	kg	3.52E+01 7.06E+00	4.48E+00	4.68E+00 7.23E-02	1.52E+02	4.65E-01 1.12E-01	-2.90E+01		
					nium ore	kg mg	6.60E-04	2.54E+00 2.33E-04	7.23E-02 3.39E-08	5.60E+01 3.91E-03	1.45E-05	-4.67E+00 -1.92E-04		
				-	Crude oil (as an	mg						1.322 04		
					ingredients)	kg	1.55E+01	0	0	8.34E+01	0	-2.46E+01		
					Iron ore	kg	2.51E+01	0	0	6.94E+01	0	-3.78E+01		
					Copper ore	kg	7.58E-01	0	0	7.38E-02	0	-2.64E-01		
	E +				Bauxite	kg	6.86E-01	0	0	2.38E+00	0	-1.23E+00		
	Resource Consumption from the environment	Exhaustible		-	Nickel ore Chromium ore	kg	8.15E-02	0	0	1.21E-01	0	-8.12E-02		
	Consu	zhau		-	Manganese ore	kg kg	1.18E-01 1.36E-01	0	0	1.88E-01 3.88E-01	0	-1.23E-01 -3.96E-02		
	the er		Material		Plumbous ore	кg kg	3.23E-01	0	0	<u>3.88E-01</u> 0	0	- <u>3.96E-02</u> -1.01E-02		
	esou rom 1			-	Tin ore	kg	0.202 02	0	0	0	0 0	0		
	~ ~				Zinc ore	kg	3.18E-01	Ő	0	0	ů 0	-9.96E-02		
					Gold ore	kg	0	0	0	0	0	0		
					Silver ore	kg	0	0	0	0	0	0		
					Silica sand	kg	1.60E+00	0	0	8.71E-01	0	-6.66E-01		
Se					Rock salt	kg	7.49E+00	2.24E-04	0	4.76E+00	1.63E-02	-4.64E+00		
Jalys				<b>—</b>	Limestone Natural soda ash	kg	5.38E+00	0	0	1.47E+01	2.61E-01	-6.40E+00		
Inventory analyses		_		- r	Wood	kg kg	1.39E-01 1.29E+01	0	0	3.83E-03 1.32E+02	0	-4.57E-02 -5.81E+01		
vento		Renewable resources			Water	kg	1.59E+04	2.70E+03	3.79E-01	5.95E+04	1.78E+02	-7.86E+03		
5					CO2	kg	2.14E+02	3.08E+01	1.52E+01	1.06E+03	2.60E+01	-1.93E+02		
		to Atmosphere			SOx	kg	1.38E-01	2.10E-02	8.48E-03	6.31E-01	1.39E-02	-1.12E-01		
					NOx	kg	2.68E-01	2.21E-02	5.87E-02	1.38E+00	3.36E-02	-2.60E-01		
					N2O	kg	1.78E-02	3.42E-03	2.74E-03	1.22E-01	4.34E-05	-1.65E-02		
					CH4	kg	1.75E-03	6.23E-04	9.07E-08	1.04E-02	3.89E-05	<u>-4.93E-04</u>		
					CO NMVOC	kg	3.58E-02 3.43E-03	4.67E-03 1.22E-03	1.27E-02 1.78E-07	2.09E-01 2.04E-02	7.07E-03 7.61E-05	-3.24E-02		
	<u>e</u> +				CxHy	kg kg	9.07E-03	7.24E-03	1.96E-07	2.04E-02 3.94E-02	1.90E-04	<u>-9.65E-04</u> -8.72E-03		
	charg			-	dust	kg	3.06E-02	8.98E-04	5.94E-03	1.09E-01	1.95E-03	-3.02E-02		
	Emission/Discharge to the environment				BOD	kg	-	-	-	-	-	-		
	nissio the e				COD	kg	-	_	-	-	_	_		
	to Er	to W	ater system		N total	kg	-	-	-	-	-	-		
					P total	kg	-	-	-		-	-		
				11-00	SS	kg	-	-	-	-	-	-		
				Uns	pecified solid waste Slag	kg kg	1.67E+00 8.08E+00	1.02E-03 0	0	6.43E+01 2.13E+01	1.98E+01 0	<u>-2.46E+00</u> -1.13E+01		
		to So	il system	-	Sludge	kg kg	1.13E+00	0	0	5.11E+00	0	-2.50E+00		
				ra	Low emission adioactive waste	kg	4.62E-04	1.63E-04	2.37E-08	2.73E-03	1.01E-05	-1.35E-04		
	sumption			(cr	nergy resources ude oil equivalent)	kg	6.93E+01	1.17E+01	4.77E+00	3.29E+02	8.56E-01	-5.93E+01		
nent	by Resource Consumption		austible sources	M	lineral resources on ore equivalent)	kg	2.63E+02	0	0	2.48E+02	0	-1.74E+02		
sesn	uo				Global warming	kg	2.18E+02	3.17E+01	1.60E+01	1.09E+03	2.60E+01	-1.98E+02		
ass	mpti		to	-	(CO2 equivalent) Acidification	kg	3.26E-01	3.65E-02	4.95E-02	1.60E+00	3.74E-02	-2.94E-01		
Impact assesment	Consur		osphere		(SO2 equivalent)	кġ	3.202-01	3.0JE-02	4.550-02	1.002+00	5.74C-UZ	-2.340-01		
	Emision Consumption		Water system											
	by En		to Soil system											

[Notes for readers: EcoLeaf common rules]

- . I. Stage related
- A. "Production" stage is intended for two sub-stages listed below.
- (1) "Raw material" production: consists of mining, transportation and raw material production.
- (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal/recycle of consumables
- /maintenance goods (e.g. replacement parts). D. "Disposition/Recycle" stage is intended for environmental impacts by product disposition/recycle, and deduction by recycling
- (e.g. impact reduction of raw material production).
   E. "Recycle Effect" illustrates an indirect environmental influences to other product/services by use of reclaimed materials/parts, and/or by supply of used products to other businesses for material reclaim/parts reuse.
- Case 1: Use of reclaimed materials/parts: Sum of increase of environmental impact by collection activities of used materials/parts, and decrease by volume reduction of used materials/parts.
- Case 2: Supply of used products to other businesses for material reclaim/parts reuse: Sum of increase of environmental impact by materials/parts reclaiming process, and decrease by volume reduction of new materials/parts production.

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore. B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate,
- which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

#### III Impact analyses

- Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO2 in case of "Global Warming")
- A. Impact "by resource consumption" represents magnitude of impacts to resource depletion. B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.
- IV Data entry format
- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results. C. Indicate "-" if calculation nor estimation can not be done, in order to differentiate to indicate "zero"
- (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

- [Notes for readers: Target product specific] A."Raw material" in "Production" includes environmental impacts generated during mining transportation material production phases of the main body of the printer and the toner cartridge enclosed in the printer. The environmental impacts are calculated using the eco-leaf basic unit DB for calculations.
- B. " Product" in "production" includes environmental impacts of processing of the parts (injection, blow-, press- and glass-molding). The environmental impacts from the parts assembly plant which is different from the main body assembly plant (such parts are clacified in "parts C") are calculated using the eco-leaf basic unit DB for calculations. The impacts from the main body assembly plant are calculated using the quantitative data on environmental impacts in our assembly plant.
- C. Regarding the basis and the basic units for calculations during distribution stages The total distance of the transportation in Japan of 100km is used according to PCR (AD-04) and the transportation overseas includes the transportation by track in China and by ship between China and Japan.

#### D. Regarding the basis and the basic units for calculations during use and consumption stage

The power consumption is measured by the TEC test procedure according to PCR (AD-04). 866,400 sheets are printed in total during the use period of five years. The toner consumption is summed up over the five years from the toner consumption data per sheet using our print pattern with 5% coverage. The production loads and the collection & recycling impacts of the toner cartridges used over the five years are included in this stage.

- E. The recycling impacts are calculated assuming that 40% of the end-of-life printers are recovered from users according to PCR (AD-04). The impacts are calculated with the remaining 60% following the disposal senario as general wastes.
- F. The impacts of material production of recycled materials are included in the values with minus as a recycling effect.

Form3 (F-03-03) Document control no. Product vendor	(	duct data sheet Input data and parameters for LCA F-03-03 INICAMINOLTA,INC.	N)				R 1/1 9/2	
EcoLeaf registration no.		AD-17-853				http://www.j	emai.or (p	
PCR name	EP and IJ printer	(PCR-ID:AD-04)	Product type	bizhub C3851				
LCA/LCIA in units of:	1	Product weight[kg]	49.2	Package[kg]	8.9	Weight total[kg]	58.1	
Product information (per unit): pa	arts etc. by material and	by process/assembly method						
	Breakdown of primar			Math breakdown of parts, which need to apply Processing / Assembly Base Units (Par				
Material name	Material name Weight (kg) Material name		Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)	
Ordinary steel	2.39E+01	Rubber	3.12E-01	Press molding:lron	2.21E+01			
Stainless steel	5.13E-01	Semiconductor circuit board	1.60E+00	Press molding:Nonfe rrous metal	1.08E+00			
Aluminium	4.98E-01			Injection molding	2.03E+01			
Other metals	5.87E-01							
Glass	1.19E+00							
Thermoplastic resin	2.11E+01	2.11E+01						
Wood	Wood 4.30E+00							
Paper	4.02E+00							
Subtotal	5.62E+01	Subtotal	1.91E+00					
	Total		E 01E+01	Cultated	4 945-01	Subtotal		

 5.82E+01
 Subtotal
 1.91E+00

 Total
 5.81E+01
 Subtotal
 4.34E+01

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site. SOx and NOx should be indicated in SO2, NO2 equivalent.

nption	Classification	Energy	Energy	Material	Material				
	Distribution	Electricity	Furnace urban	Industrial	Groundwater				
5	Distribution	(kWh)	gas (m <sup>3</sup> )	water(kg)	(kg)				
Consi	Quantity	1.26E+01	1.03E+00	2.72E+01	6.42E+01				
0	Note								
	Classification	To Water							
Emission/ Discharge		system							
cha	Distribution	Sewage(kg)							
Dis	Quantity	3.87E+01							
	Note								
3. Distribu	Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.								
	Means of transportation	Freight by ship	Diesel truck	Diesel truck					
Distribution	means or transportation	Freight by ship	:20ton	:2ton					
Libu	Conditions	Load(kg · km)	Load(kg•km)	Load(kg · km)					
Dis	Quantity	2.56E+05	2.68E+04	1.50E+03					
	Note								

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance. 4.1 Product and accessories subject to this analysis

4.1 Produ	let and accessories subject to tr	lis analysis							
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
ŭ	Distribution	Electricity	Gasoline as	Furnace urban	Industrial	Groundwater	Ordinary steel	Stainless steel	Al
Product	Distribution	(kWh)	fuel(kg)	gas (m <sup>3</sup> )	water(kg)	(kg)	(kg)	(kg)	Aluminium (kg)
2	Quantity	6.59E+02	1.76E+00	2.47E+01	4.91E+01	2.57E+03	6.67E+01	7.59E-01	2.25E+00
	Note								
	Classification	Consumption	Consumption	Consumption	Processing	Processing	Processing	Processing	Assembly
Product	Distribution	Thermoplastic resin(kg)	Paper(kg)	Rubber (kg)	Press:Iron (kg)	Press: Nonferrous(kg)	Injection molding(kg)	Blow molding (kg)	Parts assembly(kg)
ā	Quantity	8.66E+01	5.70E+01	1.15E+00	8.40E+01	2.67E+00	5.02E+00	6.11E+01	6.11E+01
	Note								
Ŧ	Classification	To Water system							
Product	Distribution	Sewage(kg)							
	Quantity	1.71E+03							
	Note								
	Classification	Distribution	Distribution	Distribution					
Product	Distribution	Freight by ship (kg·km)	Diesel truck: 20ton (kg•km)	Diesel truck: 10ton (kg•km)					
_	Quantity	1.61E+05	1.07E+05	1.91E+04					
	Note								
4.2 Dispo	sition/Recycle information on co	onsumables and	replacement par	rts					
	Classification	Consumption	Consumption	Treatment	Treatment	Treatment	Treatment	Treatment	Treatment
Consumables	Distribution	Electricity (kWh)	Kerosene(kg)	Recycle: to iron(kg)	Recycle: to Aluminum(kg)	Recycle: to plastics(kg)	Recycle: to Paper(kg)	Industrial waste destruction by fire(kg)	Industrial waste inning(kg)
õ	Quantity	3.54E+00	7.76E-02	2.70E+01	9.02E-01	2.04E+01	2.61E+01	8.44E-01	2.09E-01
	Note								
	Classification	Treatment	Treatment	Deduction	Deduction	Deduction	Deduction		
Consumables	Distribution	Waste destruction by fire(kg)	Waste inning(kg)	lron(kg)	Aluminum(kg)	Plastics(kg)	Paper(kg)		
Co	Quantity	7.06E+01	4.73E+01	-2.70E+01	-9.02E-01	-2.04E+01	-2.61E+01		
	Note								
	Classification	Distribution	Distribution						
Consumables	Distribution	Diesel truck: 10ton (kg•km)	Diesel truck: 4ton (kg•km)						
Cor	Quantity	9.43E+03	1.09E+04						
Cor	Quantity Note	9.43E+03	1.09E+04						

## 5. Disposition/Recycle stage information (per product): process method and scenarios

ş	Classification	Consumption	Consumption	Treatment	Treatment	Treatment	Treatment	Treatment	Treatment
sumables	Distribution	Electricity (kWh)	Kerosene(kg)	Recycle: to iron(kg)	Recycle: to Aluminum(kg)	Recycle: to copper(kg)	Recycle: to Glass(kg)	Recycle: to plastics(kg)	Recycle: to Paper(kg)
Consul	Quantity	1.05E+00	2.31E-02	9.91E+00	1.99E-01	4.53E-01	4.75E-01	8.37E+00	3.55E+00
0	Note								
	Classification	Treatment	Treatment	Treatment	Treatment	Deduction	Deduction	Deduction	Deduction
nsumables	Distribution	Incineration: Industrial waste(kg)	Landfill: Industrial waste(kg)	Incineration to landfill (as ash)(kg)	Landfill: General waste(kg)	lron(kg)	Aluminium (kg)	copper(kg)	Glass(kg)
Const	Quantity	5.32E-01	1.38E-01	1.79E+01	1.69E+01	-9.91E+00	-1.99E-01	-4.53E-01	-4.75E-01
	Note								
	Classification	Deduction	Deduction	Distribution	Distribution				
Consumables	Distribution	Plastics(kg)	Paper(kg)	Diesel truck: 10ton (kg•km)	Diesel truck: 4ton (kg•km)				
S	Quantity	-8.37E+00	-3.55E+00	2.81E+03	3.40E+03				
	Note								

6. Others

A.Product information:

All the parts mass per unit sorted by materials and by processes/assembly are included. The motor mass is included in ordinary steel.

B.Production site information:

The energy consumption & material use during the main body assemby and cartridge & toner shipment are included. The environmental impacts that are exhausted from the production site in the atmosphere and the water system are included.

C.Distribution stage information: The total distance of the transportation in Japan of 100km is used according to PCR (AD-04) and the transportation overseas includes the transportation by track in China and by ship between China and Japan.

D. Product and accessories subject to this analysis:

The power consumption is calculated assuming the use period of five years and 866,400 sheets printed during the use period according to the PCR (AD-04).

The toner consumption is summed up over the five years from the toner consumption data per sheet using our print pattern with 5% coverage.

The production impacts of the cartridges and toner used during the use period of five years are included.

The impacts of the maintenance parts used and the transportation impacts of the maintenace during the use period of five years are included in this stage.

### E. Disposal/Recycle information on the consumables and the maintenance parts during use stage:

The recycling information of the toner, the developer, the drums and the maintainance parts used during the use period of five years

The recycling mornator of the toner, the developer, the developer, the developer, the developer and the maintainance parts used during the das period of the years are included . The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus. Treatment of copper and deduction of copper include copper of " assembled circuit board" . Incineration of assembled circuit board is included "Incineration: Industrial waste".

### F.Disposal/Recycle stage information:

The information on the products recovered from users is included.

The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus. Treatment of copper and deduction of copper include copper of " assembled circuit board". Incineration of assembled circuit board is included "Incineration: Industrial waste".